

XLED PRO 240 SL weiss



Product code **4007841057725**

E-Nr. **924702420**

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80
- Including corner wall mount
- Interconnectable via DALI, max. 15 slaves?/master

neva
lux

199 x 180 x 161 mm



XLED PRO 240 SL weiss

Product code **4007841057725**
E-Nr. **924702420**

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Variant	white	Colour temperature	4000 K	Impact resistance	IK00
DIMENSIONS		LED colour deviation	SDCM3	Protection class (IP)	IP44
Dimensions L x W x H	199 x 180 x 161 mm	Colour rendering index	80-89	Protection class	II
ELECTRICAL		With illuminant	Yes, STEINEL LED system	Housing material	Plastic
Mains connection	230 – 240 V	Illuminant	LED cannot be replaced	Cover material	Plastic, opal
Power	20 W	Luminous flux	1830 lm	SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LIFETIME		Manufacturer warranty	5 years
Max. mounting height	6,00 m	LED lifetime max. °C	60000 h	Corner wall bracket included	Yes
With motion detector	No	Luminous flux decline per LM80	L70B10		

XLED PRO 240 SL weiss

Product code **4007841057725**
E-Nr. **924702420**

Illustrations

MOUNTING HEIGHT



XLED PRO 240 SL weiss

Product code **4007841057725**
E-Nr. **924702420**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841003630	XLED PRO 240 weiss	

ORDERING INFORMATION

Art.-Nr.

4007841057725

E-Number

924702420

Typ

XLED PRO 240 SL weiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss