

RS PRO Connect R20 SL warmweiss



Product code **4007841057091**

E-Nr. **941301339**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Backlight function
- Optional main light level 50 - 100%
- Modern plug-in terminals for straightforward installation

neva
lux

350 x 55 mm



RS PRO Connect R20 SL warmweiss

Product code **4007841057091**
E-Nr. **941301339**

Technical Data

IDENTIFICATION		With illuminant		Yes, STEINEL LED system	Base light function detail		LED Backlight
Variant	warm white	Illuminant		LED cannot be replaced	Functions		Backlight
DIMENSIONS		Base		without	Settings via		Bluetooth
Dimensions Ø × H	350 x 55 mm	LED cooling system		Passive Thermo Control	With remote control		No
ELECTRICAL		Soft light start		Yes	HOUSING & MATERIAL		
Mains connection	220 – 240 V / 50 – 60 Hz	Continuous light		selectable	Impact resistance		IK07
Power	16 W	Luminous flux		1950 lm	Protection class (IP)		IP40
SENSOR TECHNOLOGY		LIFETIME			Protection class		II
With motion detector	No	LED lifetime max. °C		50000 h	Ambient temperature		-20 – 40 °C
LIGHTING TECHNOLOGY		Luminous flux decline per LM80		L80B50	Housing material		Plastic
Colour temperature	3000 K	LED lifespan (25 °C)		60000 h	Cover material		PC, opal
LED colour deviation	SDCM3	SETTINGS			SCOPE OF DELIVERY & WARRANTY		
Colour rendering index	80-89	Twilight switch		No	Manufacturer warranty		5 years

RS PRO Connect R20 SL warmweiss

Product code **4007841057091**
E-Nr. **941301339**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841057107	RS PRO Connect R20 warmweiss	

ORDERING INFORMATION

Art.-Nr.

4007841057091

E-Number

941301339

Typ

RS PRO Connect R20 SL warmweiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss