elani connect P1500 3K

PENDANT LUMINAIRE CONNECT

Product code **221123**

- Built-in, networkable light management for next generation lighting projects
- up to 70% energy savings compared to a conventional solution thanks to constant light control and presence detection
- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

1500 x 60 x 80 mm



elani connect P1500 3K

PENDANT LUMINAIRE CONNECT

Product code **221123**

Technical Data

DIMENSIONS

Dimensions L × W × H	**1500 x 60 x 80 mm**

ELECTRICAL

Mains connection	**200…240 V / 50 – 60 Hz**
Power	**47 W**

SENSOR TECHNOLOGY

With motion detector	**Nein**

CONNECTIVITY

Control technology	**Smartlink Connect**
Wireless networking via	**BT SIG Mesh**

LIGHTING TECHNOLOGY

Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80-89**
Illuminant	**LED**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Protection class	**I**
Ambient temperature	**-20…45 °C**
Housing material	**Aluminium**
Cover material	**Acrylglas opal**
Mounting type	**Decke Pendel**
Colour	**Aluminium**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

CERTIFICATES & EPREL

EPREL energy efficiency class	**D**


elani connect P1500 3K

PENDANT LUMINAIRE CONNECT

Product code **221123**

Illustrations

TECHNICAL DRAWINGS



1500 x 60 x 80 mm


elani connect P1500 3K

PENDANT LUMINAIRE CONNECT

Product code **221123**


Wiring Diagrams

WIRING DIAGRAM 1



Wiring diagram networking wire

WIRING DIAGRAM 2



Wiring diagram networking radio

elani connect P1500 3K

PENDANT LUMINAIRE CONNECT

Product code **221123**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	221100	**elani Diffusor 1500 CDP**	Microprismatic Diffuser 1500mm
	221343	**elani Connector 90°**	90° connection with miter cut
	221570	**Connect TK2 BLM**	Pushbutton interface 2gang
	221107	**elani Link**	Connection of luminaires
	221106	**elani Color RAL_NCS_1500**	Special paint 1.5m
	221109	**Connect PD**	Presence detector installed on the side
	221591	**Smartlink T-Board PB4**	Mobile push-button board
	221970	**Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2**	Wireless push-button, battery-free

elani connect P1500 3K

PENDANT LUMINAIRE CONNECT

Product code **221123**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	221996	**elani WM-Set 2B**	Wall mounting kit

ORDERING INFORMATION

Art.-Nr.	221123
Typ	**elani connect P1500 3K**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss