

IS 130-2 silber

neva
lux

Product code 4007841660116

E-Nr. 535996860

- UV-resistant plastic

neva
lux

87 x 78 x 110 mm



IS 130-2 silber

Product code **4007841660116**

E-Nr. **535996860**

Technical Data

IDENTIFICATION	
Version	Motion detectors
DIMENSIONS	
Dimensions L x W x H	87 x 78 x 110 mm
ELECTRICAL	
Mains connection	230 – 240 V / 50 Hz
Power	600 W
Switching output 1 resistive	600 W
Fluorescent lamps ECG	430 W
Fluorescent lamps uncompensated	500 VA
Fluorescent lamps series-compensated	500 VA
Fluorescent lamps parallel-compensated	500 VA
Switching output 1 low-voltage halogen lamps	500 VA
LED lamps < 2 W	16 W
LED lamps > 2 W < 8 W	64 W
LED lamps > 8 W	64 W
Capacitive load in µF	88 µF
Switching output 1 number of LED/fluorescent lamps	4 pcs.
SENSOR TECHNOLOGY	
Max. mounting height	3,00 m

Sensor technology	passive infrared
Detection angle	130 °
Opening angle	40 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	r = 3 m (10 m²)
Tangential range	r = 12 m (163 m²)
Switching zones	260 switching zones
Mounting height	1,80 – 3,00 m
Optimal mounting height	2 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master
Networking via	Cable
LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable
Constant light regulation	No
SETTINGS	
Twilight switch	Yes

Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Base light function	No
Main light adjustable	No
Settings via	Potentiometers
With remote control	No
Twilight setting teach	No
HOUSING & MATERIAL	
Protection class (IP)	IP54
Ambient temperature	-20 – 50 °C
Mounting location	wall
Application location	Indoors Outdoors
Mounting type	Surface wiring
Material	Plastic
Application room	all round the building courtyard & driveway front door outdoors terrace / balcony
Colour	Silver
RAL colour	9006
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	3 years
Corner wall bracket included	No

IS 130-2 silber

Product code **4007841660116**
E-Nr. **535996860**

Illustrations

MOUNTING HEIGHT

1,80 – 3,00 m BEREICH	2 m OPTIMAL	3,00 m MAX
--------------------------	----------------	---------------

IS 130-2 silber

Product code **4007841660116**
E-Nr. **535996860**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841660116
E-Number	535996860
Typ	IS 130-2 silber
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	