

zwena connect HF P450 4K

ZWENA CONNECT P

neva
lux

Product code **222054**

- For universal use for illumination of offices, schools, traffic zones, etc.
- Optionally as an intelligent Connect version with or without motion sensor, or as a conventional DALI luminaire
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- High quality finish
- Direct and indirect light distribution

neva
lux

450 x 82 mm



zwena connect HF P450 4K

Product code 222054

ZWENA CONNECT P

Technical Data

DIMENSIONS		CONNECTIVITY		Direct/indirect ratio separately controllable	No
Dimensions Ø x H	450 x 82 mm	With radio network control	Yes	With program-controlled lighting control	Yes
Suspension length	1500 mm	LIGHTING TECHNOLOGY		Constant light output control	Yes
ELECTRICAL		Colour temperature	4000 K	HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	LED colour deviation	SDCM3	Protection class (IP)	IP20
Power	30 W	Colour rendering index	80-89	Protection class	I
Replaceable driver	Yes	Illuminant	LED	Ambient temperature	-20...45 °C
Type of wiring	Suitable for through wiring	Luminous flux	3100 lm (Down 2100, Up 1000)	Housing material	Aluminum
LED rated current	800 mA	Beam angle	Down 95°, Up 100°	Cover material	Microprismatic acrylic glass
SENSOR TECHNOLOGY		Luminaire luminous efficacy	103 lm/W	Mounting type	Ceiling pendant
Sensor technology	High frequency	Glare value	UGR < 18	Colour	white
With motion detector	Yes	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
Radial range	Ø 8 m (50 m²)	SETTINGS		CERTIFICATES & EPREL	
Tangential range	Ø 8 m (50 m²)	DALI dimming	Yes	EPREL energy efficiency class	E
Mounting height	< 4 m	With emergency light	No		
With light sensor	Yes				

zwena connect HF P450 4K

Product code 222054

ZWENA CONNECT P

Illustrations

MOUNTING HEIGHT

< 4 m

BEREICH

zwena connect HF P450 4K

Product code 222054

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221753	Emergency Package 1h (50V/1.5W/Compact/PS)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222054

Typ

zwena connect HF P450 4K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss