

zwena DALI P350 4K

ZWENA CONNECT P

neva
lux

Product code **220578**

- For universal use for illumination of offices, schools, traffic zones, etc.
- Optionally as an intelligent Connect version with or without motion sensor, or as a conventional DALI luminaire
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- High quality finish
- Direct and indirect light distribution

neva
lux

350 x 82 mm



zwena DALI P350 4K

ZWENA CONNECT P

Product code 220578

Technical Data

DIMENSIONS					
Dimensions Ø × H	350 x 82 mm	LED colour deviation	SDCM3	Direct/indirect ratio separately controllable	No
Suspension length	1500 mm	Colour rendering index	80-89	HOUSING & MATERIAL	
ELECTRICAL		Illuminant	LED	Protection class (IP)	IP20
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	1700 lm (Down 1200, Up 500)	Protection class	I
Power	18 W	Beam angle	Down 95°, Up 100°	Ambient temperature	-20...45 °C
Replaceable driver	Yes	Luminaire luminous efficacy	94 lm/W	Housing material	Aluminum
Type of wiring	Suitable for through wiring	Glare value	UGR < 18	Cover material	Microprismatic acrylic glass
LED rated current	450 mA	LIFETIME		Mounting type	Ceiling pendant
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Colour	white
With motion detector	No	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
With light sensor	No	DALI dimming	Yes	Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		With emergency light	No	CERTIFICATES & EPREL	
Colour temperature	4000 K			EPREL energy efficiency class	F

zwena DALI P350 4K

ZWENA CONNECT P

Product code 220578

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220580	zwena DALI P450 4K	
 220582	zwena DALI P600 4K	
 220584	zwena DALI P900 4K	
 220692	Emergency Package 1h (50V/1.5W/Compact)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220578

Typ

zwena DALI P350 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss