

XLED home 2 XL SL graphit



Product code OLD-4007841030094

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80

neva
lux

199 x 180 x 161 mm



XLED home 2 XL SL graphit

Product code **OLD-4007841030094**

Technical Data

IDENTIFICATION				SETTINGS	
Variant	graphite	LED colour deviation	SDCM3	Twilight switch	No
DIMENSIONS		Colour rendering index	80-89	Base light function	No
Dimensions L x W x H	199 x 180 x 161 mm	With illuminant	Yes, STEINEL LED system	HOUSING & MATERIAL	
ELECTRICAL		Illuminant	LED cannot be replaced	Impact resistance	IK00
Mains connection	230 – 240 V , 50 / 60 Hz	LED cooling system	HCMC (High Conductive Magnesium Composite)	Protection class (IP)	IP44
Power	20 W	Continuous light	selectable	Protection class	II
SENSOR TECHNOLOGY		Luminous flux	1608 lm	Ambient temperature	-20 – 40 °C
Max. mounting height	4,00 m	LIFETIME		Housing material	HCMC
With motion detector	No	LED lifetime max. °C	50000 h	Cover material	Plastic, opal
LIGHTING TECHNOLOGY		Luminous flux decline per LM80	L70B10	SCOPE OF DELIVERY & WARRANTY	
Colour temperature	4000 K			Manufacturer warranty	5 years

XLED home 2 XL SL graphit

Product code **OLD-4007841030094**

Illustrations

MOUNTING HEIGHT



XLED home 2 XL SL graphit

Product code **OLD-4007841030094**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841053086	Eckwandhalter XLED Home 2/ Protect/ Pro 240/ PRO Expanse graphit	Accessory

ORDERING INFORMATION

Art.-Nr.

OLD-4007841030094

Typ

XLED home 2 XL SL graphit

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss