

elani C2400 TW

ELANI

neva
lux

Product code **221137**

- For universal use for lighting offices, schools, traffic zones etc.
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

2400 x 60 x 80 mm



elani C2400 TW

Product code 221137

ELANI

Technical Data

DIMENSIONS		Colour rendering index		HOUSING & MATERIAL	
Dimensions L x W x H	2400 x 60 x 80 mm	80-89		Protection class (IP)	IP20
ELECTRICAL		Illuminant		Protection class	II
Mains connection	200...240 V / 50 – 60 Hz	Yes, LED-System		Ambient temperature	-20...45 °C
Power	60 W	Luminous flux		Housing material	Aluminium
Replaceable driver	Yes	6720 lm		Cover material	Acrylic glass opal
Type of wiring	Suitable for through wiring	Beam angle		Mounting type	Ceiling / wall surface-mounted
SENSOR TECHNOLOGY		105°		Colour	Aluminium
With motion detector	No	Luminaire luminous efficacy		SCOPE OF DELIVERY & WARRANTY	
With light sensor	No	112 lm/W		Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		Glare value		CERTIFICATES & EPREL	
Colour temperature	3000...5600 K	UGR < 24		EPREL energy efficiency class	E
LED colour deviation	SDCM3	LIFETIME			
		LED lifespan (25 °C)			
		50000 h			
		SETTINGS			
		DALI dimming			
		Yes			
		With emergency light			
		No			
		Suitable for light band configuration			
		Yes			

elani C2400 TW

ELANI

Product code 221137

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221101	elani Diffusor 2500 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221396	elani Color RAL_NCS_2400	Other
 221107	elani Link	Coupler/connector straight
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221137

Typ

elani C2400 TW

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss