

IS 345 LiveLink - Unterputz rund

neva
lux

Product code 4007841049447

E-Nr. 535955367

neva
lux

124 x 78 mm



IS 345 LiveLink - Unterputz rund

Product code **4007841049447**
E-Nr. **535955367**

Technical Data

IDENTIFICATION			
Variant	LiveLink - concealed installation, round	Segment-by-segment masking	Yes
Version	Motion detectors	Electronic scalability	No
Model	LiveLink	Mechanical scalability	No
DIMENSIONS		Radial range	12 x 6 m (72 m²)
Dimensions Ø x H		Tangential range	23 x 6 m (138 m²)
124 x 78 mm		Switching zones	280 switching zones
ELECTRICAL		Mounting height	2,50 – 5,00 m
Mains connection	230 V, 50 / 60 Hz	Optimal mounting height	2,8 m
Supply voltage detail	DALI bus	CONNECTIVITY	
Livelihood values	Light level, Motion detection, Presence detection	Networking	Yes
SENSOR TECHNOLOGY		Number of DALI participants	3
Sensor technology	passive infrared	LIGHTING TECHNOLOGY	
Detection angle	360 °	Constant light regulation	No
Opening angle	45 °	SETTINGS	
Sneak-under protection	Yes	Twilight setting	2 – 1000 lx
		Time setting	5 sec – 15 min
		Base light function	No
		With remote control	No
		Twilight setting teach	Yes
		HOUSING & MATERIAL	
		Protection class (IP)	IP20
		Ambient temperature	-20 – 50 °C
		Mounting location	ceiling
		Application location	Indoors Outdoors
		Mounting type	Concealed wiring
		Material	Plastic
		Colour	white
		RAL colour	9003
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		OTHER	
		Application, location, room	corridor, aisle, underground car park, multi-storey car park

IS 345 LiveLink - Unterputz rund

Product code **4007841049447**
E-Nr. **535955367**

Illustrations

MOUNTING HEIGHT

2,50 – 5,00 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

IS 345 LiveLink - Unterputz rund

Product code **4007841049447**
E-Nr. **535955367**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841049447
E-Number	535955367
Typ	IS 345 LiveLink - Unterputz rund
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	