XLED home 2 Z-Wave white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841029821

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80

194 x 180 x 161 mm



XLED home 2 Z-Wave white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841029821

Technical Data

IDENTIFICATION

Variant	white

DIMENSIONS

Dimensions L × W × H	194 x 180 x 161 mm

ELECTRICAL

Mains connection	230 – 240 V , 50 / 60 Hz
Power	14,8 W

SENSOR TECHNOLOGY

Sensor technology	passive infrared
With motion detector	Yes
Detection angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Tangential range	r = 14 m (239 m²)
Transmission range	Up to 100 m in the open, 30 m indoors

CONNECTIVITY

Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
LED cooling system	HCMC (High Conductive Magnesium Composite)
Luminous flux	1184 lm

LIFETIME

LED lifetime max. °C	50000 h
Luminous flux decline per LM80	L70B10

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	8 sec – 35 min

HOUSING & MATERIAL

Impact resistance	IK00
Protection class (IP)	IP44
Protection class	II
Housing material	HCMC
Cover material	Plastic, opal

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

XLED home 2 Z-Wave white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841029821

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841029876	**Smartfriends Box**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841029821
EAN	4007841029821
Typ	**XLED home 2 Z-Wave white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss