

RS 160 LED Glas

neva
lux

Product code **4007841053987**

E-Nr. **941000009**

- Including STEINEL LED system
- 4-hour manual override (optional)
- High-quality opal glass shade
- Facility for connecting fan

neva
lux

310 x 125 mm



RS 160 LED Glas

Product code **4007841053987**
E-Nr. **941000009**

Technical Data

DIMENSIONS		CONNECTIVITY		SETTINGS	
Dimensions Ø × H	310 x 125 mm	Networking	Yes	Twilight switch	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		Twilight setting	2 – 2000 lx
Mains connection	220 – 240 V , 50 / 60 Hz	Colour temperature	3000 K	Time setting	5 sec – 15 min
Power	9,5 W	LED colour deviation	SDCM3	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		Colour rendering index	90-100	Impact resistance	IK00
Sensor technology	High frequency	Illuminant	LED cannot be replaced	Protection class (IP)	IP44
Transmission power	< 1 mW	Base	without	Protection class	II
With motion detector	Yes	LED cooling system	Passive Thermo Control	Ambient temperature	-10 – 40 °C
Detection	also through glass, wood and stud walls	Continuous light	selectable, 4h	Housing material	Glass
Detection angle	360 °	Luminous flux	1000 lm	Cover material	Glass opal
Opening angle	160 °	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Electronic scalability	Yes	LED lifetime max. °C	50000 h	Manufacturer warranty	3 years
Mechanical scalability	No	Luminous flux decline per LM80	L70B10		

RS 160 LED Glas

Product code **4007841053987**
E-Nr. **941000009**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841055899	L 16 LED Glas	
 4007841055905	L 160 LED Glas	

ORDERING INFORMATION

Art.-Nr.

4007841053987

E-Number

941000009

Typ

RS 160 LED Glas

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss