

nayo P Diffused 4K

NAYO P DIFFUSED 4K

neva
lux

Product code 220463

- High luminaire efficiency with 120 lm/W
- Direct and indirect light distribution
- Diffuser optics for large-area illumination (UGR < 19)
- Link technology for seamless extension of the light profile with connectors
- Dimmable DALI, LiveLink compatible
- Housing Aluminium RAL9016, white

neva
lux

1190 x 160 x 30 mm



nayo P Diffused 4K

NAYO P DIFFUSED 4K

Product code 220463

Technical Data

DIMENSIONS			
Dimensions L x W x H	1190 x 160 x 30 mm		
Suspension length	1500 mm		
ELECTRICAL			
Mains connection	200...240 V / 50 – 60 Hz		
Power	60 W		
Replaceable driver	Yes		
Type of wiring	Through wiring included		
SENSOR TECHNOLOGY			
With motion detector	No		
With light sensor	No		
LIGHTING TECHNOLOGY			
Colour temperature	4000 K		
LED colour deviation	SDCM3		
Colour rendering index	80-89		
ILLUMINANT	LED		
Luminous flux	7200 lm (Down 3600, Up 3600)		
Beam angle	Down 105°, Up 115°		
Luminaire luminous efficacy	120 lm/W		
Glare value	UGR < 19		
LIFETIME			
LED lifespan (25 °C)	50000 h		
SETTINGS			
DALI dimming	Yes		
With emergency light	No		
Suitable for light band configuration	Yes		
Direct/indirect ratio separately controllable	No		
Constant light output control	Yes		
HOUSING & MATERIAL			
Protection class (IP)	IP20		
Protection class	I		
Ambient temperature	-20...45 °C		
Housing material	Aluminum		
Cover material	Microprismatic acrylic glass		
Mounting type	Ceiling pendant		
Colour	white		
SCOPE OF DELIVERY & WARRANTY			
Manufacturer warranty	5 years		
CERTIFICATES & EPREL			
EPREL energy efficiency class	E		

nayo P Diffused 4K

NAYO P DIFFUSED 4K

Product code **220463**

Accessories

ORDERING INFORMATION

Art.-Nr. 220463

Typ nayo P Diffused 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss