RS M1 S Stainless steel

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841052492
E-Nr. 941301129

- Indoor light with motion detector in square design for elegant accents
- With pleasant ambient light for a beautiful room atmosphere, suitable for ceiling and wall mounting
- Automatic light thanks to hidden 360° high-frequency sensor with up to Ø8 m detection on movement
- Functions: adjustable basic light, 4 hours continuous light
- Warm white light (3000 K) and long-life 8,8 W LEDs with 759 lm
- Incl. mounting accessories - plastic-free packaging

steinel

53 x 200 x 200 mm



RS M1 S Stainless steel

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841052492**
E-Nr. **941301129**

Technical Data

DIMENSIONS

Dimensions L × W × H	**53 x 200 x 200 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Power	**8,8 W**
Own consumption	**0,39 W**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**High frequency**
Transmission power	**< 1 mW**
HF technology	**5,8 GHz**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 8 m (50 m²)**
Tangential range	**Ø 8 m (50 m²)**
Mounting height	**2 – 4 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Measured luminous flux 360°	**759 lm**
Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
Base	**without**
LED cooling system	**Passive Thermo Control**
Soft light start	**No**
Continuous light	**selectable, 4h**

LIFETIME

LED lifetime max. °C	**60000 h**
Luminous flux decline per LM80	**L70B10**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 15 Min.**
Base light function	**Yes**
Base light function time	**10/30 min, all night**
Settings via	**Potentiometers**
With remote control	**No**
Twilight setting teach	**No**
Base light function in percent	**10 %**
Base light function percent from	**10 %**

HOUSING & MATERIAL

Impact resistance	**IK03**
Protection class (IP)	**IP20**
Protection class	**II**
Ambient temperature	**from -10 up to 30 °C**
Housing material	**Plastic**
Cover material	**Plastic, opal**
Mounting location	**ceiling wall**
Application location	**Indoors**
Mounting type	**Surface wiring**
Application room	**Indoors WC / washroom corridor / aisle function room / ancillary room outdoors stairwell**
Colour	**white**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**

CERTIFICATES & EPREL

Certificates	**DEKRA**


RS M1 S Stainless steel

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841052492**
E-Nr. **941301129**

Illustrations

TECHNICAL DRAWINGS



53 x 200 x 200 mm

MOUNTING HEIGHT

2 – 4 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX


RS M1 S Stainless steel

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841052492**
E-Nr. **941301129**

Wiring Diagrams

WIRING DIAGRAM 1




Circuit diagram

RS M1 S Stainless steel

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841052492**
E-Nr. **941301129**

Highlights



Including STEINEL LED system



LED ambient light



4-hour manual override (optional)



Optional basic lighting level 10 %



High-quality materials

RS M1 S Stainless steel

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841052492**
E-Nr. **941301129**

Accessories

ORDERING INFORMATION

Art.-Nr.	052492
EAN	4007841052492
E-Number	941301129
Typ	**RS M1 S Stainless steel**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss