RS PRO 5150 SC V2 with motion detector - 4000K

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841091477
E-Nr. 941386049

- Long field luminaire, 1500 mm, with integrated digital high-frequency sensor
- Ideal for renovating car parks, halls or garages
- Easy conversion thanks to sliding bracket
- 360° motion detection with ø8 m range, 3-wire through-wiring
- Precise adjustment of range and sensitivity
- Dimmable basic and main light from 10-100%
- All settings and networking easily via the free Steinel Connect app
- Suitable for connection to central battery

steinel

1500 x 87 x 58 mm



RS PRO 5150 SC V2 with motion detector - 4000K

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841091477
E-Nr. 941386049

Technical Data

IDENTIFICATION

Type of accessory	Other

DIMENSIONS

Dimensions L × W × H	1500 x 87 x 58 mm

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Power	42 W
Own consumption	0,45 W

SENSOR TECHNOLOGY

Max. mounting height	3,50 m
Sensor technology	High frequency
With motion detector	Yes
Detection angle	360 °
Opening angle	160 °
Electronic scalability	Yes
Mounting height	3,50 m

CONNECTIVITY

Networking	Yes
Control technology	Steinel Connect

LIGHTING TECHNOLOGY

Measured luminous flux 360°	5940 lm
Colour temperature	4000 K
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced

LIFETIME

LED lifetime max. °C	60000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10

SETTINGS

Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	Yes
Base light function time	1-60 min
Main light adjustable	0 - 100 %
Functions	Encrypted communication Neighbouring group function Free selection of the light value in a luminaire group Adjustable fade time when switching on and off Connection to central battery systems Motions sensor Light sensor Orientation light
Base light function in percent	10 – 100 %
Base light function percent from	10 %

HOUSING & MATERIAL

Impact resistance	IK07
Protection class (IP)	IP65
Protection class	II
Ambient temperature	from -20 up to 40 °C
Housing material	Plastic
Cover material	Plastic, structured
Mounting location	ceiling wall
Material	Plastic
Colour	grey

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

CERTIFICATES & EPREL

Certificates	DEKRA


RS PRO 5150 SC V2 with motion detector - 4000K

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841091477**
E-Nr. **941386049**

Illustrations

TECHNICAL DRAWINGS



1500 x 87 x 58 mm

MOUNTING HEIGHT

3,50 m BEREICH	3,50 m MAX


RS PRO 5150 SC V2 with motion detector - 4000K

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841091477**
E-Nr. **941386049**


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/slave and master/master interconnection circuit diagram

RS PRO 5150 SC V2 with motion detector - 4000K

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841091477**
E-Nr. **941386049**

Accessories

ORDERING INFORMATION

Art.-Nr.	091477
EAN	4007841091477
E-Number	941386049
Typ	**RS PRO 5150 SC V2 with motion detector - 4000K**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss