

US 360 LiveLink

neva
lux

Product code 4007841008444

- Optional surface-mounting adapter
- Optional guard cage

neva
lux

120 x 120 x 68 mm



US 360 LiveLink

Product code 4007841008444

Technical Data

IDENTIFICATION				HOUSING & MATERIAL	
Variant	LiveLink	Electronic scalability	Yes	Protection class (IP)	IP20
Version	Presence detector	Mechanical scalability	No	Mounting location	ceiling
Model	LiveLink	Radial range	Ø 10 m (79 m²)	Application location	Indoors
DIMENSIONS		Tangential range	Ø 10 m (79 m²)	Mounting type	Concealed wiring
Dimensions L x W x H	120 x 120 x 68 mm	Mounting height	2,50 – 3,50 m	Material	Plastic
ELECTRICAL		Presence range	Ø 6 m (28 m²)	Colour	white
Supply voltage detail	DALI bus	US technology	40 kHz	RAL colour	9010
Livelink values	Light level, Motion detection	Optimal mounting height	2,8 m	SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		CONNECTIVITY		Manufacturer warranty	5 years
Sensor technology	Ultrasonic	With bus coupler	Yes	OTHER	
Detection angle	360 °	SETTINGS		Application, location, room	classroom, One-person office, Open-plan office, conference room, side room, stairwell, washroom, wc, equipment room
Opening angle	180 °	Twilight setting	10 – 1000 lx		
Sneak-under protection	Yes	Time setting	60 sec – 60 min		
		Settings via	LiveLink app		
		Twilight setting teach	Yes		

US 360 LiveLink

Product code 4007841008444

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL
---	-------------------------------------

US 360 LiveLink

Product code 4007841008444

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841008444

Typ

US 360 LiveLink

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss