RS PRO R30 Q basic SC Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841067878
E-Nr. 941002699

steinel

350 x 350 x 55 mm



RS PRO R30 Q basic SC Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841067878
E-Nr. 941002699

Technical Data

DIMENSIONS

Dimensions L × W × H	350 x 350 x 55 mm

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Power	23,4 W
Own consumption	0,3 W

SENSOR TECHNOLOGY

Max. mounting height	4,00 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 10 m (79 m²)
Tangential range	Ø 10 m (79 m²)
Mounting height	2,00 – 4,00 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master
Slave mode adjustable	Yes
Control technology	Steinel Connect
Wireless networking via	BT SIG Mesh

LIGHTING TECHNOLOGY

Measured luminous flux 360°	2964 lm
Colour temperature	4000 K
LED colour deviation	SDCM3
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable

LIFETIME

LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B50

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	Yes
Base light function detail	LED Backlight
Base light function time	1-60 min
Main light adjustable	0 - 100 %
Functions	Group parameterisation Manual ON / ON-OFF Neighbouring group function Orientation light Motions sensor Light sensor Encrypted communication Free selection of the light value in a luminaire group Adjustable fade time when switching on and off
Settings via	Bluetooth
With remote control	No
Twilight setting teach	Yes
Base light function in percent	0 – 100 %
Base light function percent from	0 %

HOUSING & MATERIAL

Impact resistance	IK07
Protection class (IP)	IP40
Protection class	II
Ambient temperature	from -20 up to 40 °C
Housing material	Plastic
Cover material	PC, opal
Mounting location	ceiling wall
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Application room	Indoors changing room corridor / aisle function room / ancillary room kitchenette stairwell
Colour	white

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
House number sheet included	No

CERTIFICATES & EPREL

EPREL category	Surrounded product with integrated light source


RS PRO R30 Q basic SC Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841067878**
E-Nr. **941002699**

Illustrations

TECHNICAL DRAWINGS



350 x 350 x 55 mm

MOUNTING HEIGHT

2,00 – 4,00 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX


RS PRO R30 Q basic SC Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT


EAN **4007841067878**
E-Nr. **941002699**

Wiring Diagrams

WIRING DIAGRAM 1



WIRING DIAGRAM 2




RS PRO R30 Q basic SC Neutral white


SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841067878
E-Nr. 941002699


Highlights




Including STEINEL LED system



Interconnectable and adjustable via Bluetooth



Impact-resistant material rated to IK07



Metal shrouds for defining the direction of sensor detection




Optional basic lighting level 0 - 100 %



Adjustable main light brighness (0 - 100%)



Optional emergency light



Modern plug-in terminals for straightforward installation

RS PRO R30 Q basic SC Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841067878
E-Nr. 941002699

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841087234	**Adapter R-Serie für Notlichtweiche**	Accessory
	4007841064143	**Notlicht-Modul R-Serie**	Accessory
	4007841084653	**Funktaster PB2-Bluetooth**	System components
	4007841084660	**Funktaster PB4-Bluetooth**	System components
	221386	**Universal P-Set 3S**	Universal pendant set with 3 ropes
	4007841067335	**Relais REL5A-Bluetooth**	System components
	4007841067342	**Tasterkoppler PC4-Bluetooth**	System components
	4007841064914	**Ersatzakku für Notlicht R-Serie**	Spare Part

ORDERING INFORMATION

Art.-Nr.	067878
EAN	4007841067878
E-Number	941002699
Typ	**RS PRO R30 Q basic SC Neutral white**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss