

IS 3360 MX Highbay LiveLink - Aufputz eckig

neva
lux

Product code 4007841009724

E-Nr. 535946460

neva
lux

95 x 95 x 65 mm



IS 3360 MX Highbay LiveLink - Aufputz eckig

Product code **4007841009724**
E-Nr. **535946460**

Technical Data

IDENTIFICATION	
Variant	LiveLink - surface-mounted, square
Version	Motion detectors
Model	LiveLink
DIMENSIONS	
Dimensions L x W x H	95 x 95 x 65 mm
ELECTRICAL	
Mains connection	16 V
Supply voltage detail	DALI bus
SENSOR TECHNOLOGY	
Sensor technology	passive infrared
Detection angle	360 °
Opening angle	45 °
Segment-by-segment masking	Yes
Electronic scalability	No

Radial range	Ø 14 m (154 m²)
Tangential range	Ø 36 m (1018 m²)
Switching zones	1416 switching zones
Mounting height	4,00 – 14,00 m
Optimal mounting height	12 m
CONNECTIVITY	
Networking	Yes
Number of DALI participants	3
LIGHTING TECHNOLOGY	
Constant light regulation	Yes
SETTINGS	
Twilight setting	2 – 1000 lx
Time setting	60 sec – 60 min
Base light function	No
Settings via	LiveLink app

With remote control	No
Twilight setting teach	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP54
Ambient temperature	-20 – 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Colour	white
RAL colour	9003
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
OTHER	
Application, location, room	high-bay warehouse, sports hall

IS 3360 MX Highbay LiveLink - Aufputz eckig

Product code 4007841009724
E-Nr. 535946460

Illustrations

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL
---------------------------	-----------------

IS 3360 MX Highbay LiveLink - Aufputz eckig

Product code **4007841009724**
E-Nr. **535946460**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841009724
E-Number	535946460
Typ	IS 3360 MX Highbay LiveLink - Aufputz eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	