

RS PRO P2 EM flat S Emergency light - warm white

neva
lux**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN 4007841069728

E-Nr. 941003539

 **steinel**

322 x 68 mm



RS PRO P2 EM flat S Emergency light - warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069728
E-Nr. 941003539

Technical Data

DIMENSIONS	
Dimensions Ø × H	322 x 68 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	15,1 W
Switching output 1 low-voltage halogen lamps	800 VA
LED lamps > 8 W	250 W
Capacitive load in µF	88 µF
Switching output 1 number of LED/fluorescent lamps	50 pcs.
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m
Sensor technology	High frequency
With motion detector	Yes
Detection angle	360 °
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)
Mounting height	2 – 4 m
Optimal mounting height	2,8 m
CONNECTIVITY	
Networking	Yes
Networking via	Cable
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	1608 lm
Colour temperature	3000 K
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Luminous flux emergency light	38 lm
LIFETIME	
LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10
SETTINGS	
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Base light function	Yes
Base light function time	10/30 min, all night
Main light adjustable	No
Functions	Emergency light in compliance with EN 60598-2-22 for 3h
Base light function in percent	10 %
Base light function percent from	10 %
HOUSING & MATERIAL	
Impact resistance	IK03
Protection class (IP)	IP54
Protection class	II
Ambient temperature	from -10 up to 30 °C
Housing material	Plastic
Cover material	Plastic, opal
Mounting location	ceiling wall
Colour	white
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	DEKRA
EPREL category	Surrounded product with integrated light source


RS PRO P2 EM flat S Emergency light - warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069728
E-Nr. 941003539

Illustrations

TECHNICAL DRAWINGS



322 x 68 mm

MOUNTING HEIGHT

2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------	------------------	---------------


RS PRO P2 EM flat S Emergency light - warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069728
E-Nr. 941003539


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

RS PRO P2 EM flat S Emergency light - warm white

SENSOR-SWITCHED LED INDOOR LIGHT


EAN 4007841069728

E-Nr. 941003539

Highlights



Including STEINEL LED system



Intelligent soft light start



Interconnectable by cable (maximum of 10 units)



Optional basic lighting level 10 %

RS PRO P2 EM flat S Emergency light - warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069728
E-Nr. 941003539

Accessories

ORDERING INFORMATION	
Art.-Nr.	069728
EAN	4007841069728
E-Number	941003539
Typ	RS PRO P2 EM flat S Emergency light - warm white

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss