HF 360-2 DALI-2 Input Device - surface

PRESENCE DETECTOR

EAN 4007841086602
E-Nr. 535903142

- Perfect radial detection with a range of up to 25 m, ideal for long corridors and hallways
- Customisable range that can be set individually in both directions
- Control PRO II design for a modern and functional look that enables versatile applications
- Bluetooth technology for simple connection and control via Bluetooth
- Multiple interfaces, compatible with COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD
- External light measurement required for black sensors that can be integrated via Bluetooth or KNX

steinel

57 x 123 x 123 mm



HF 360-2 DALI-2 Input Device - surface

PRESENCE DETECTOR

EAN **4007841086602**
E-Nr. **535903142**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**57 x 123 x 123 mm**

ELECTRICAL

Mains connection	**12 – 23 V**
Supply voltage detail	**DALI bus**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**High frequency**
Transmission power	**< 1 mW**
HF technology	**5,8 GHz**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 12 m (113 m²)**
Tangential range	**Ø 12 m (113 m²)**
Mounting height	**2,5 – 4 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
With bus coupler	**Yes**
Control technology	**Steinel Connect**
Wireless networking via	**BT SIG Mesh**
Networking via	**DALI 2**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Base light function	**No**
Main light adjustable	**No**
Settings via	**Bluetooth Mesh**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -25 up to 50 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Application room	**Indoors WC / washroom function room / ancillary room kitchenette stairwell**
Colour	**white**
RAL colour	**9003**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**

CERTIFICATES & EPREL

Certificates	**DALI-2**


HF 360-2 DALI-2 Input Device - surface

PRESENCE DETECTOR

EAN **4007841086602**
E-Nr. **535903142**

Illustrations

TECHNICAL DRAWINGS



57 x 123 x 123 mm

MOUNTING HEIGHT

2,5 – 4 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX


HF 360-2 DALI-2 Input Device - surface

PRESENCE DETECTOR

EAN 4007841086602
E-Nr. 535903142

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

HF 360-2 DALI-2 Input Device - surface

PRESENCE DETECTOR

EAN **4007841086602**
E-Nr. **535903142**

Highlights



UV-resistant plastic

HF 360-2 DALI-2 Input Device - surface

PRESENCE DETECTOR

EAN **4007841086602**
E-Nr. **535903142**

Accessories

ORDERING INFORMATION

Art.-Nr.	086602
EAN	4007841086602
E-Number	535903142
Typ	**HF 360-2 DALI-2 Input Device - surface**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss