IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN 4007841065942
E-Nr. 535900046

- Passive infrared presence detector with square 360° detection
- 5.200 switching zones for the finest detection
- Offers the largest detection range in our IR range
- 4 pyro sensors individually de- / activatable
- Sensitivity digitally adjustable
- Measures presence and brightness
- Temperature and humidity measurement with IP, KNX and DALI-2 IPD
- Setting and networking via Bluetooth
- Ideal for open-plan offices and classrooms

steinel

64 x 123 x 123 mm



IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN **4007841065942**
E-Nr. **535900046**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**64 x 123 x 123 mm**

ELECTRICAL

Mains connection	**24 – 55 V**
Own consumption	**0,3 W**
Supply voltage detail	**Passive PoE SELV, standard PoE (IEEE 802.3 af)**

SENSOR TECHNOLOGY

Max. mounting height	**10,00 m**
Sensor technology	**passive infrared**
Detection angle	**360 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**Yes**
Mechanical scalability	**Yes**
Radial range	**9 x 9 m (81 m²)**
Tangential range	**24 x 24 m (576 m²)**
Mounting height	**2,50 – 10,00 m**
Presence range	**9 x 9 m (81 m²)**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
With bus coupler	**Yes**
Control technology	**Steinel Connect**
Wireless networking via	**BT SIG Mesh**
Networking via	**IP / IT**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Base light function	**No**
Main light adjustable	**No**
Functions	**Motions sensor Presence function Presence detector logic**
Settings via	**Bluetooth Web-Interface**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from 0 up to 40 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Application room	**Indoors changing room classroom conference room / meeting room dining hall / staff restaurant duty room high-bay warehouse lecture hall multi-storey / underground car park open-plan office production facilities reception / lobby recreation room sports hall**
Colour	**white**
RAL colour	**9003**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN **4007841065942**
E-Nr. **535900046**

Illustrations

TECHNICAL DRAWINGS



64 x 123 x 123 mm

MOUNTING HEIGHT

2,50 – 10,00 m	2,8 m	10,00 m
BEREICH	OPTIMAL	MAX


IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN **4007841065942**
E-Nr. **535900046**

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN 4007841065942
E-Nr. 535900046

Highlights



UV-resistant plastic

IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN **4007841065942**
E-Nr. **535900046**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841067335	**Relais REL5A-Bluetooth**	System components
	4007841067342	**Tasterkoppler PC4-Bluetooth**	System components

ORDERING INFORMATION

Art.-Nr.	065942
EAN	4007841065942
E-Number	535900046
Typ	**IR Quattro HD-2 24m IP - surface**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss