

XLED PRO Wide S weiss



Product code **4007841010072**

E-Nr. **924700260**

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level
- UV resistant material
- Interconnectable by cable
- RC9 remote control optional
- Smart Remote remote control optional

neva
lux

126 x 265 x 188 mm



XLED PRO Wide S weiss

Product code **4007841010072**
E-Nr. **924700260**

Technical Data

DIMENSIONS		LIGHTING TECHNOLOGY		Twilight setting teach		Yes
Dimensions L × W × H	126 x 265 x 188 mm	Measured luminous flux 360°	2400 lm	Base light function in percent	3 %	
ELECTRICAL		Colour temperature	4000 K	Base light function percent from	3 %	
Mains connection	220 – 240 V / 50 – 60 Hz	LED colour deviation	SDCM3	HOUSING & MATERIAL		
Power	24,8 W	Colour rendering index	80-89	Impact resistance	IK03	
SENSOR TECHNOLOGY		With illuminant	Yes, STEINEL LED system	Protection class (IP)	IP54	
Max. mounting height	6,00 m	Illuminant	LED cannot be replaced	Protection class	I	
Sensor technology	passive infrared	Base	without	Ambient temperature	-20 – 40 °C	
With motion detector	Yes	LED cooling system	Passive Thermo Control	Housing material	Aluminium	
Detection angle	240 °	Soft light start	No	Cover material	Plastic, transparent	
Opening angle	180 °	Continuous light	selectable, 4h	Cover material (scope of delivery)	sticker	
Sneak-under protection	Yes	LIFETIME		Mounting location	wall	
Segment-by-segment masking	Yes	LED lifetime max. °C	50000 h	Application location	Outdoors	
Electronic scalability	No	Luminous flux decline per LM80	L70B10	Mounting type	Surface wiring	
Mechanical scalability	No	SETTINGS		Application room	courtyard & driveway outdoors	
Radial range	r = 3 m (19 m²)	Twilight switch	Yes	Colour	white	
Tangential range	r = 12 m (302 m²)	Twilight setting	2 – 1000 lx	SCOPE OF DELIVERY & WARRANTY		
Mounting height	1,80 – 6,00 m	Time setting	5 s – 15 Min.	Manufacturer warranty	5 years	
Optimal mounting height	2 m	Base light function	Yes	Corner wall bracket included	No	
CONNECTIVITY		Base light function time	10 min\n30 min\nall night	CERTIFICATES & EPREL		
Networking	Yes	Main light adjustable	No	Certificates	VDE	
Type of networking	Sensor/slave	Settings via	Remote control\nPotentiometers\nSmart Remote			
Networking via	Cable					
Networking quantity	maximum of 10 floodlights					

XLED PRO Wide S weiss

Product code **4007841010072**
E-Nr. **924700260**

Illustrations

MOUNTING HEIGHT

1,80 – 6,00 m BEREICH	2 m OPTIMAL	6,00 m MAX
--------------------------	----------------	---------------

XLED PRO Wide S weiss

Product code **4007841010072**
E-Nr. **924700260**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841007638	Fernbedienung RC9	Other

ORDERING INFORMATION

Art.-Nr.

4007841010072

E-Number

924700260

Typ

XLED PRO Wide S weiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss