

IS 360-1 DE inox

neva
lux

Product code 4007841034917

E-Nr. 535942730

- UV-resistant plastic

neva
lux

78 x 89 mm



IS 360-1 DE inox

Product code **4007841034917**
E-Nr. **535942730**

Technical Data

IDENTIFICATION	
Version	Motion detectors
DIMENSIONS	
Dimensions Ø × H	78 x 89 mm
ELECTRICAL	
Mains connection	230 – 240 V / 50 – 60 Hz
Power	1000 W
Switching output 1 resistive	1000 W
Fluorescent lamps ECG	430 W
Fluorescent lamps uncompensated	500 VA
Fluorescent lamps series-compensated	406 VA
Fluorescent lamps parallel-compensated	406 VA
Switching output 1 low-voltage halogen lamps	1000 VA
LED lamps < 2 W	16 W
LED lamps > 2 W < 8 W	64 W
LED lamps > 8 W	64 W
Capacitive load in µF	132 µF
Switching output 1 number of LED/fluorescent lamps	6 pcs.
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m

Sensor technology	passive infrared
Detection angle	360 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	Ø 4 m (13 m²)
Tangential range	Ø 8 m (50 m²)
Switching zones	304 switching zones
Mounting height	2,50 – 4,00 m
Optimal mounting height	2,5 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master
Networking via	Cable
LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable
Constant light regulation	No
SETTINGS	
Twilight switch	Yes

Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Base light function	No
Main light adjustable	No
Settings via	Potentiometers
With remote control	No
Twilight setting teach	No
HOUSING & MATERIAL	
Protection class (IP)	IP54
Protection class	II
Ambient temperature	-20 – 40 °C
Mounting location	ceiling
Application location	Indoors Outdoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	Indoors all round the building front door outdoors terrace / balcony
Colour	Silver
RAL colour	9006
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	3 years
Corner wall bracket included	No

IS 360-1 DE inox

Product code **4007841034917**
E-Nr. **535942730**

Illustrations

MOUNTING HEIGHT

2,50 – 4,00 m BEREICH	2,5 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

IS 360-1 DE inox

Product code **4007841034917**
E-Nr. **535942730**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841034917
E-Number	535942730
Typ	IS 360-1 DE inox
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	