

RS PRO Connect R10 SL neutralweiss



Product code **4007841057053**

E-Nr. **941001839**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Backlight function
- Optional main light level 50 - 100%
- Modern plug-in terminals for straightforward installation

neva
lux

300 x 55 mm



RS PRO Connect R10 SL neutralweiss

Product code **4007841057053**
E-Nr. **941001839**

Technical Data

IDENTIFICATION		With illuminant	Yes, STEINEL LED system	Base light function detail	LED Backlight
Variant	Neutral white	Illuminant	LED cannot be replaced	Functions	Backlight
DIMENSIONS		Base	without	Settings via	Bluetooth
Dimensions Ø x H	300 x 55 mm	LED cooling system	Passive Thermo Control	With remote control	No
ELECTRICAL		Soft light start	No	HOUSING & MATERIAL	
Mains connection	220 – 240 V / 50 – 60 Hz	Continuous light	selectable	Impact resistance	IK07
Power	9 W	Luminous flux	1130 lm	Protection class (IP)	IP40
SENSOR TECHNOLOGY		LIFETIME		Protection class	II
With motion detector	No	LED lifetime max. °C	55000 h	Ambient temperature	-20 – 40 °C
LIGHTING TECHNOLOGY		Luminous flux decline per LM80	L80B50	Housing material	Plastic
Colour temperature	4000 K	LED lifespan (25 °C)	60000 h	Cover material	PC, opal
LED colour deviation	SDCM3	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
Colour rendering index	80-89	Twilight switch	No	Manufacturer warranty	5 years

RS PRO Connect R10 SL neutralweiss

Product code **4007841057053**
E-Nr. **941001839**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841057046	RS PRO Connect R10 neutralweiss	

ORDERING INFORMATION

Art.-Nr.

4007841057053

E-Number

941001839

Typ

RS PRO Connect R10 SL neutralweiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss