US 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN 4007841059514
E-Nr. 535933340

steinel

66 x 120 x 120 mm



US 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841059514**
E-Nr. **535933340**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**66 x 120 x 120 mm**

ELECTRICAL

Mains connection	**24 – 29 V**
Supply voltage detail	**KNX bus**

SENSOR TECHNOLOGY

Max. mounting height	**2,80 m**
Sensor technology	**Ultrasonic**
With motion detector	**Yes**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 10 m (79 m²)**
Tangential range	**Ø 6 m (28 m²)**
Mounting height	**2,50 – 2,8 m**
Presence range	**Ø 6 m (28 m²)**
US technology	**40 kHz**
Optimal mounting height	**3,5 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master Master/slave**
KNX functions	**Photo-cell controller Basic light level function Light level HVAC output Constant-lighting control Light output 4x Presence output Day / night function Logic gate**
With bus coupler	**Yes**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Soft light start	**Yes**
Continuous light	**selectable**
Constant light regulation	**Yes**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**10 – 1000 lx**
Time setting	**10 s – 1092 Min.**
Base light function	**Yes**
Base light function time	**1-30 min, all night**
Main light adjustable	**0 - 100 %**
Settings via	**ETS software Remote control Bus Smart Remote**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -20 up to 55 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed wiring**
Material	**Plastic**
Application room	**Indoors WC / washroom classroom conference room / meeting room duty room function room / ancillary room one-person office open-plan office recreation room stairwell**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


US 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841059514**
E-Nr. **535933340**

Illustrations

TECHNICAL DRAWINGS



66 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 2,8 m BEREICH	3,5 m OPTIMAL	2,80 m MAX

US 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841059514**
E-Nr. **535933340**


Highlights




Optional remote controls



Smart Remote remote control optional



Optional surface-mounting adapter



Optional guard cage

US 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841059514**
E-Nr. **535933340**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841000363	**Aufputz-Adapter Control Pro IP54 weiss**	Accessory
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841593018	**Service Fernbedienung RC6 KNX**	Accessory
	4007841592912	**Nutzer Fernbedienung RC7 KNX**	Accessory

ORDERING INFORMATION

Art.-Nr.	059514
EAN	4007841059514
E-Number	535933340
Typ	**US 360 KNX - Concealed wiring**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss