IS 3360 MX Highbay LiveLink - surface-mounted, square

MOTION DETECTOR

EAN 4007841009724
E-Nr. 535946460

95 x 95 x 65 mm



IS 3360 MX Highbay LiveLink - surface-mounted, square

MOTION DETECTOR

EAN 4007841009724
E-Nr. 535946460

Technical Data

IDENTIFICATION

Variant	LiveLink - surface-mounted, square
Version	Motion detectors
Model	LiveLink

DIMENSIONS

Dimensions L × W × H	95 x 95 x 65 mm

ELECTRICAL

Mains connection	16 V
Supply voltage detail	DALI bus

SENSOR TECHNOLOGY

Sensor technology	passive infrared
Detection angle	360 °
Opening angle	45 °
Segment-by-segment masking	Yes
Electronic scalability	No
Radial range	Ø 14 m (154 m²)
Tangential range	Ø 36 m (1018 m²)
Switching zones	1416 switching zones
Mounting height	4,00 – 14,00 m
Optimal mounting height	12 m

CONNECTIVITY

Networking	Yes
Number of DALI participants	3
Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Constant light regulation	Yes

SETTINGS

Twilight setting	2 – 1000 lx
Time setting	60 sec – 60 min
Base light function	No
Settings via	LiveLink app
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP54
Ambient temperature	-20 – 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

OTHER

Application, location, room	high-bay warehouse, sports hall

IS 3360 MX Highbay LiveLink - surface-mounted, square

MOTION DETECTOR

EAN 4007841009724
E-Nr. 535946460

Illustrations

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL

IS 3360 MX Highbay LiveLink - surface-mounted, square

MOTION DETECTOR

EAN **4007841009724**
E-Nr. **535946460**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841009724
EAN	4007841009724
E-Number	535946460

Typ **IS 3360 MX Highbay LiveLink - surface-mounted, square**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss