

RS PRO 5100 C Notlicht

neva
lux

Product code **4007841058708**

E-Nr. **941000069**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Optional basic lighting level 10 - 50 %
- Optional main light level 50 - 100%
- Adjustable mounts for easy installation
- Emergency light module in compliance with EN 60598-2-22

neva
lux

58 x 1370 x 87 mm



RS PRO 5100 C Notlicht

Product code **4007841058708**
E-Nr. **941000069**

Technical Data

DIMENSIONS	
Dimensions L x W x H	58 x 1370 x 87 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	32 W
Own consumption	0,41 W
SENSOR TECHNOLOGY	
Max. mounting height	3,50 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 10 m (79 m²)
Tangential range	Ø 10 m (79 m²)
Mounting height	2,00 – 3,5 m
Optimal mounting height	3 m
CONNECTIVITY	
Networking	Yes
Networking via	Bluetooth
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	4206 lm

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	No
Continuous light	selectable
Luminous flux emergency light	687 lm
LIFETIME	
LED lifetime max. °C	60000 h
Luminous flux decline per LM80	L80B10
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 60 min
Base light function	Yes
Base light function time	10-30 min, all night
Main light adjustable	50 - 100 %
Functions	Group parameterisation\nManual ON / ON-OFF\nMaster/slave override\nNeighbouring group function\nPresence function\nEmergency light in compliance with EN 60598-2-22 for 3h
Settings via	Bluetooth

With remote control	Yes
Twilight setting teach	Yes
Base light function in percent	10 – 50 %
Base light function percent from	10 %
HOUSING & MATERIAL	
Impact resistance	IK07
Protection class (IP)	IP66
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, structured
Mounting location	ceiling wall
Application location	Indoors
Mounting type	Surface wiring
Application room	Indoors WC / washroom changing room corridor / aisle function room / ancillary room kitchenette outdoors stairwell
Colour	grey
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	DEKRA

RS PRO 5100 C Notlicht

Product code **4007841058708**
E-Nr. **941000069**

Illustrations

MOUNTING HEIGHT

2,00 – 3,5 m BEREICH	3 m OPTIMAL	3,50 m MAX
-------------------------	----------------	---------------

RS PRO 5100 C Notlicht

Product code **4007841058708**
E-Nr. **941000069**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841058708
E-Number	941000069
Typ	RS PRO 5100 C Notlicht

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss