

RS PRO 5150 SC mit Bewegungsmelder & Bluetooth Verso

neva
lux**RS PRO 5100 UND 5150****Product code 221393****E-Nr. 941006369**

- Inklusive STEINEL LED-System
- Vernetzbar und Einstellbar via Bluetooth
- Schlagfestes Material IK 07
- Optionale Grundhelligkeit 10 - 50 %
- Optionales Hauptlicht 50 - 100 %
- Verschiebbare Halter für einfache Montage

neva
lux

1500 x 87 x 58 mm



RS PRO 5150 SC mit Bewegungsmelder & Bluetooth Verso

Product code 221393
E-Nr. 941006369

RS PRO 5100 UND 5150

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Base light function in percent		10 – 100 %	
Type of accessory	Other	Measured luminous flux 360°	5940 lm	Base light function percent from		10 %	
DIMENSIONS		Colour temperature	4000 K	HOUSING & MATERIAL			
Dimensions L x W x H	1500 x 87 x 58 mm	Colour rendering index	90-100	Impact resistance		IK07	
ELECTRICAL		Illuminant	LED cannot be replaced	Protection class (IP)		IP66	
Mains connection	220 – 240 V / 50 – 60 Hz	LIFETIME		Protection class		II	
Power	42 W	LED lifetime max. °C	60000 h	Ambient temperature		-20 – 40 °C	
Own consumption	0,45 W	Luminous flux decline per LM80	L80B10	Housing material		Plastic	
SENSOR TECHNOLOGY		SETTINGS		Cover material		Plastic, structured	
Max. mounting height	4,00 m	Twilight setting	2 – 2000 lx	Material		Plastic	
Sensor technology	High frequency	Time setting	5 sec – 60 min	Colour		grey	
With motion detector	Yes	Base light function	Yes	SCOPE OF DELIVERY & WARRANTY			
Detection	also through glass, wood and stud walls	Base light function time	1-60 min	Manufacturer warranty		5 years	
Detection angle	360 °	Main light adjustable	10 - 100 %	CERTIFICATES & EPREL			
Opening angle	160 °	Functions	Encrypted communicationPresence functionOrientation lightNeighbouring group functionLight sensorFree selection of the light value in a luminaire groupAdjustable fade time when switching on and offMotions sensorConnection to central battery systems	Certificates		DEKRA	
Electronic scalability	Yes			EPREL category		Umgebenes Produkt mit integrierter Lichtquelle	
Mechanical scalability	No						
Radial range	Ø 10 m (79 m²)						
Tangential range	Ø 10 m (79 m²)						
Mounting height	2,00 – 4,00 m						
CONNECTIVITY		With remote control		Yes			
Networking	Yes						

RS PRO 5150 SC mit Bewegungsmelder & Bluetooth Verso

RS PRO 5100 UND 5150

Product code 221393
E-Nr. 941006369

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	4,00 m MAX
--------------------------	---------------

RS PRO 5150 SC mit Bewegungsmelder & Bluetooth Verso

RS PRO 5100 UND 5150

Product code 221393
E-Nr. 941006369

Accessories

ORDERING INFORMATION	
Art.-Nr.	221393
E-Number	941006369
Typ	RS PRO 5150 SC mit Bewegungsmelder & Bluetooth Verso
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	