

HF 3360 LiveLink - Unterputz eckig

neva
lux

Product code 4007841055622

E-Nr. 535939307

neva
lux

94 x 94 x 64 mm



HF 3360 LiveLink - Unterputz eckig

Product code 4007841055622
E-Nr. 535939307

Technical Data

IDENTIFICATION					
Variant	LiveLink - concealed installation, square	Electronic scalability	Yes	With remote control	No
Version	Motion detectors	Mechanical scalability	No	Twilight setting teach	Yes
Model	LiveLink	Radial range	Ø 8 m (50 m²)	HOUSING & MATERIAL	
DIMENSIONS		Tangential range	Ø 8 m (50 m²)	Protection class (IP)	IP20
Dimensions L x W x H	94 x 94 x 64 mm	Mounting height	2,00 – 4,00 m	Ambient temperature	-20 – 50 °C
ELECTRICAL		Optimal mounting height	2,8 m	Mounting location	ceiling corner wall
Mains connection	230 V, 50 / 60 Hz	CONNECTIVITY		Application location	Indoors
Livelink values	Light level, Motion detection	Networking	Yes	Mounting type	Concealed wiring
SENSOR TECHNOLOGY		Number of DALI participants	5	Material	Plastic
Sensor technology	High frequency	LIGHTING TECHNOLOGY		Colour	white
HF technology	5,8 GHz	Constant light regulation	No	RAL colour	9003
Detection	also through glass, wood and stud walls	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	Twilight setting	2 – 1000 lx	Manufacturer warranty	5 years
Opening angle	140 °	Time setting	5 sec – 15 min	OTHER	
Sneak-under protection	Yes	Base light function	No	Application, location, room side room, stairwell, wc, washroom, multi-storey car park, underground car park, equipment room	
		Settings via	LiveLink app		

HF 3360 LiveLink - Unterputz eckig

Product code **4007841055622**
E-Nr. **535939307**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

HF 3360 LiveLink - Unterputz eckig

Product code **4007841055622**
E-Nr. **535939307**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841055622
E-Number	535939307
Typ	HF 3360 LiveLink - Unterputz eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	