

fayola MF1 IP65 On-Off/Phasecut D2W

neva
lux**FAYOLA MF1 IP65****Product code 220447**

- Multi-purpose use in the private and commercial sector
- Light colour becomes warmer when dimmed
- Wide beam optics 60°, Directable 30°
- Optimized heat management, long lifetime
- Variants On-Off-Phasecut and DALI available

neva
lux

90 x 56 mm



fayola MF1 IP65 On-Off/Phasecut D2W

FAYOLA MF1 IP65

Product code 220447

Technical Data

DIMENSIONS		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Dimensions Ø × H	90 x 56 mm	Colour temperature	1800...3000 K	Protection class (IP)	IP65
Drill hole	75 mm	LED colour deviation	SDCM3	Protection class	II
ELECTRICAL		Colour rendering index	80-89	Ambient temperature	-20...40 °C
Mains connection	220...240 V / 50 – 60 Hz	Illuminant	LED	Housing material	Aluminum
Power	8 W	Luminous flux	470 lm	Cover material	Reflector aluminium
Replaceable driver	Yes	Beam angle	60°	Mounting type	In-ceiling installation
Type of wiring	Ending	Luminaire luminous efficacy	59 lm/W	Colour	white
LED rated current	350 mA	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
With motion detector	No	SETTINGS		CERTIFICATES & EPREL	
		DALI dimming	No	EPREL energy efficiency class	G

fayola MF1 IP65 On-Off/Phasecut D2W

FAYOLA MF1 IP65

Product code 220447

Accessories

ORDERING INFORMATION	
Art.-Nr.	220447
Typ	fayola MF1 IP65 On-Off/Phasecut D2W
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	