

lisha W1800 4K



Product code **221379**

- For universal use in lighting offices, schools, lobbies, traffic zones, etc.
- Convincing concept for simple and fast mounting
- Link technology for seamless extension of the continuous row with through-wiring
- Dimmable DALI
- Variants with 0.6, 1.2 and 1.8 meter length available
- Housing Aluminum White

neva
lux

1810 x 51 x 85 mm



lisha W1800 4K

Product code **221379**

Technical Data

DIMENSIONS

Dimensions L x W x H **1810 x 51 x 85 mm**

ELECTRICAL

Mains connection	200...240 V / 50 – 60 Hz
Power	50 W
Replaceable driver	Yes
Type of wiring	Through wiring included

SENSOR TECHNOLOGY

With motion detector	No
With light sensor	No

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3

Colour rendering index	80-89
Illuminant	Yes, LED-System
Luminous flux	6000 lm (Down 3000, Up 3000)
Beam angle	15° Wallwasher
Luminaire luminous efficacy	120 lm/W
Glare value	UGR < 19

LIFETIME

LED lifespan (25 °C)	50000 h
----------------------	---------

SETTINGS

DALI dimming	Yes
With emergency light	No
Suitable for light band configuration	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminium
Cover material	Microprismatic acrylic glass
Mounting type	Wall surface-mounted
Colour	white

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
-----------------------	---------


CERTIFICATES & EPREL

EPREL energy efficiency class

lisha W1800 4K

Product code 221379

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220176	lisha C1200 4K	
 220178	lisha C1200 Wallwasher 4K	
 220180	lisha P1200 4K	
 220182	lisha P1200 Wallwasher 4K	

ORDERING INFORMATION

Art.-Nr.

221379

Typ

lisha W1800 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss