

RS PRO Connect R30 Q neutralweiss



Product code **4007841057190**

E-Nr. **941301599**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Backlight function
- Optional basic lighting level 10 - 50 %
- Optional main light level 50 - 100 %
- Optional emergency light

neva
lux

55 x 350 x 350 mm



RS PRO Connect R30 Q neutralweiss

Product code **4007841057190**
E-Nr. **941301599**

Technical Data

IDENTIFICATION		CONNECTIVITY			
Variant	Neutral white	Networking	Yes	Twilight setting	2 – 2000 lx
DIMENSIONS		Type of networking	Master/slave	Time setting	5 sec – 30 min
Dimensions L x W x H	55 x 350 x 350 mm	LIGHTING TECHNOLOGY		Base light function	Yes
ELECTRICAL		Colour temperature	4000 K	Base light function detail	LED Backlight
Mains connection	220 – 240 V / 50 – 60 Hz	LED colour deviation	SDCM3	Base light function time	10-30 min, all night
Power	24,5 W	Colour rendering index	80-89	Functions	Group parameterisation, Manual ON / ON-OFF, Master/slave override, Neighbouring-group function, Presence function, Backlight
Own consumption	0,5 W	With illuminant	Yes, STEINEL LED system		
SENSOR TECHNOLOGY		Illuminant	LED cannot be replaced	Settings via	Bluetooth
Sensor technology	High frequency	Base	without	With remote control	No
Transmission power	< 1 mW	LED cooling system	Passive Thermo Control	HOUSING & MATERIAL	
HF technology	5,8 GHz	Soft light start	Yes	Impact resistance	IK07
With motion detector	Yes	Continuous light	selectable	Protection class (IP)	IP40
Detection	also through glass, wood and stud walls	Luminous flux	3150 lm	Protection class	II
Detection angle	360 °	LIFETIME		Ambient temperature	-20 – 40 °C
Opening angle	160 °	LED lifetime max. °C	50000 h	Housing material	Plastic
Segment-by-segment masking	Yes	Luminous flux decline per LM80	L80B50	Cover material	PC, opal
Electronic scalability	Yes	LED lifespan (25 °C)	60000 h	SCOPE OF DELIVERY & WARRANTY	
Mechanical scalability	No	SETTINGS		Manufacturer warranty	5 years
Radial range	Ø 10 m (79 m²)	Twilight switch	Yes		

RS PRO Connect R30 Q neutralweiss

Product code **4007841057190**
E-Nr. **941301599**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841064143	Notlicht-Modul R-Serie	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841057190

E-Number

941301599

Typ

RS PRO Connect R30 Q neutralweiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss