

HF 360 KNX - Concealed wiring

PRESENCE DETECTOR

neva
lux

EAN 4007841059484

E-Nr. 535935408

● steinel

55 x 120 x 120 mm



HF 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN 4007841059484

E-Nr. 535935408

Technical Data

IDENTIFICATION

Version	Presence detector
1.0	1.0
1.1	1.1
1.2	1.2
1.3	1.3
1.4	1.4
1.5	1.5
1.6	1.6
1.7	1.7
1.8	1.8
1.9	1.9
1.10	1.10
1.11	1.11
1.12	1.12
1.13	1.13
1.14	1.14
1.15	1.15
1.16	1.16
1.17	1.17
1.18	1.18
1.19	1.19
1.20	1.20
1.21	1.21
1.22	1.22
1.23	1.23
1.24	1.24
1.25	1.25
1.26	1.26
1.27	1.27
1.28	1.28
1.29	1.29
1.30	1.30
1.31	1.31
1.32	1.32
1.33	1.33
1.34	1.34
1.35	1.35
1.36	1.36
1.37	1.37
1.38	1.38
1.39	1.39
1.40	1.40
1.41	1.41
1.42	1.42
1.43	1.43
1.44	1.44
1.45	1.45
1.46	1.46
1.47	1.47
1.48	1.48
1.49	1.49
1.50	1.50
1.51	1.51
1.52	1.52
1.53	1.53
1.54	1.54
1.55	1.55
1.56	1.56
1.57	1.57
1.58	1.58
1.59	1.59
1.60	1.60
1.61	1.61
1.62	1.62
1.63	1.63
1.64	1.64
1.65	1.65
1.66	1.66
1.67	1.67
1.68	1.68
1.69	1.69
1.70	1.70
1.71	1.71
1.72	1.72
1.73	1.73
1.74	1.74
1.75	1.75
1.76	1.76
1.77	1.77
1.78	1.78
1.79	1.79
1.80	1.80
1.81	1.81
1.82	1.82
1.83	1.83
1.84	1.84
1.85	1.85
1.86	1.86
1.87	1.87
1.88	1.88
1.89	1.89
1.90	1.90
1.91	1.91
1.92	1.92
1.93	1.93
1.94	1.94
1.95	1.95
1.96	1.96
1.97	1.97
1.98	1.98
1.99	1.99
2.00	2.00
2.01	2.01
2.02	2.02
2.03	2.03
2.04	2.04
2.05	2.05
2.06	2.06
2.07	2.07
2.08	2.08
2.09	2.09
2.10	2.10
2.11	2.11
2.12	2.12
2.13	2.13
2.14	2.14
2.15	2.15
2.16	2.16
2.17	2.17
2.18	2.18
2.19	2.19
2.20	2.20
2.21	2.21
2.22	2.22
2.23	2.23
2.24	2.24
2.25	2.25
2.26	2.26
2.27	2.27
2.28	2.28
2.29	2.29
2.30	2.30
2.31	2.31
2.32	2.32
2.33	2.33
2.34	2.34
2.35	2.35
2.36	2.36
2.37	2.37
2.38	2.38
2.39	2.39
2.40	2.40
2.41	2.41
2.42	2.42
2.43	2.43
2.44	2.44
2.45	2.45
2.46	2.46
2.47	2.47
2.48	2.48
2.49	2.49
2.50	2.50

DIMENSIONS

Dimensions L x W x H 55 x 120 x 120 mm

ELECTRICAL

Mains connection	30 V
Own consumption	0,7 W
Supply voltage detail	KNX bus

SENSOR TECHNOLOGY

Max. mounting height	3,50 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No

Range detail

1 or 2 detection directions
can be masked out by
stickers for adjustment to
the room situation.

Radial range	Ø 12 m (113 m²)
Tangential range	Ø 12 m (113 m²)
Mounting height	2,50 – 3,5 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master Master/slave
Networking via	KNX bus
KNX functions	Photo-cell controller Basic light level function Light level HVAC output Constant-lighting control Light output 4x Presence output Day / night function Logic gate
With bus coupler	Yes

LIGHTING TECHNOLOGY

Soft light start	Yes
Continuous light	selectable
Constant light regulation	Yes

SETTINGS

Twilight switch	Yes
Twilight setting	10 – 1000 lx
Time setting	10 s – 1092 Min.
Base light function	Yes

Base light function time	1-255 min
Main light adjustable	0 - 100 %
Settings via	ETS software Remote control Bus Smart Remote
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -25 up to 55 °C
Cover material (scope of delivery)	sticker
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	Indoors WC / washroom function room / ancillary room kitchenette stairwell

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No

CERTIFICATES & EPREL

Certificates VDE

HF 360 KNX - Concealed wiring


PRESENCE DETECTOR

EAN 4007841059484

E-Nr. 535935408

Illustrations

TECHNICAL DRAWINGS



55 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 3,5 m BEREICH	2,8 m OPTIMAL	3,50 m MAX
-------------------------	------------------	---------------

HF 360 KNX - Concealed wiring

PRESENCE DETECTOR


EAN 4007841059484

E-Nr. 535935408


Highlights




Optional remote controls



Smart Remote remote control optional



HF ceiling adapter for installation in
suspended ceilings



Optional guard cage

HF 360 KNX - Concealed wiring

PRESENCE DETECTOR

EAN 4007841059484
E-Nr. 535935408

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841593018	Service Fernbedienung RC6 KNX	Other
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841006600	HF-Deckenadapter	Accessory
 4007841009151	Smart Remote	Accessory
 4007841592912	Nutzer Fernbedienung RC7 KNX	Accessory

ORDERING INFORMATION

Art.-Nr.

059484

EAN

4007841059484

E-Number

535935408

Typ

HF 360 KNX - Concealed wiring

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss