

RS PRO Connect 5100 LED 5 Core



Product code **4007841064471**

E-Nr. **941003429**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Optional basic lighting level 10 - 50 %
- Optional main light level 50 - 100%
- Adjustable mounts for easy installation

neva
lux

58 x 1370 x 87 mm



RS PRO Connect 5100 LED 5 Core

Product code **4007841064471**
E-Nr. **941003429**

Technical Data

IDENTIFICATION		Mechanical scalability		No	SETTINGS	
Variant	5 Core	Radial range	Ø 12 m (113 m²)		Twilight switch	Yes
DIMENSIONS		CONNECTIVITY			Twilight setting	2 – 2000 lx
Dimensions L x W x H	58 x 1370 x 87 mm	Networking	Yes		Time setting	5 sec – 60 min
ELECTRICAL		Type of networking	Master/master, Master/slave		Base light function	Yes
Mains connection	220 – 240 V / 50 – 60 Hz	LIGHTING TECHNOLOGY			Base light function time	10-30 min, all night
Power	30 W	Colour temperature	4000 K		Functions	Group parameterisation, Manual ON / ON-OFF, Master/slave override, Neighbouring-group function, Presence function
Own consumption	0,45 W	LED colour deviation	SDCM3		Settings via	Bluetooth
SENSOR TECHNOLOGY		Colour rendering index	80-89		With remote control	No
Sensor technology	High frequency	With illuminant	Yes, STEINEL LED system		HOUSING & MATERIAL	
Transmission power	< 1 mW	Illuminant	LED cannot be replaced		Impact resistance	IK07
HF technology	5,8 GHz	Base	without		Protection class (IP)	IP66
With motion detector	Yes	LED cooling system	Passive Thermo Control		Protection class	II
Detection	also through glass, wood and stud walls	Soft light start	No		Ambient temperature	-20 – 40 °C
Detection angle	360 °	Continuous light	selectable		Housing material	Plastic
Opening angle	160 °	Luminous flux	4206 lm		Cover material	Plastic, structured
Segment-by-segment masking	Yes	LIFETIME			SCOPE OF DELIVERY & WARRANTY	
Electronic scalability	Yes	LED lifetime max. °C	60000 h		Manufacturer warranty	5 years
		Luminous flux decline per LM80	L80B10			

RS PRO Connect 5100 LED 5 Core

Product code **4007841064471**
E-Nr. **941003429**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841052904	RS PRO 5100 C Slave	
 4007841058708	RS PRO 5100 C Notlicht	

ORDERING INFORMATION

Art.-Nr.

4007841064471

E-Number

941003429

Typ

RS PRO Connect 5100 LED 5 Core

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss