

RS PRO P2 SP warmweiss

P-SERIE

neva
lux

Product code **221808**

- Including STEINEL LED system
- Intelligent soft light start
- Interconnectable by cable (maximum of 10 units)

neva
lux

320 x 110 mm



RS PRO P2 SP warmweiss

P-SERIE

Product code 221808

Technical Data

DIMENSIONS	
Dimensions Ø × H	320 x 110 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	14 W
SENSOR TECHNOLOGY	
With motion detector	No
CONNECTIVITY	
Networking via	Cable
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	1645 lm
Colour temperature	3000 K

With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
LIFETIME	
LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10
SETTINGS	
Main light adjustable	No
HOUSING & MATERIAL	
Impact resistance	IK03

Protection class (IP)	IP54
Protection class	II
Ambient temperature	from -10 up to 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Mounting location	ceiling wall
Colour	white
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	DEKRA
EPREL category	Surrounded product with integrated light source

RS PRO P2 SP warmweiss

Product code **221808**

P-SERIE

Accessories

ORDERING INFORMATION

Art.-Nr. 221808

Typ RS PRO P2 SP warmweiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss