

L 825 LED iHF silber

neva
lux

Product code **4007841007171**

E-Nr. **924352129**

- Including STEINEL LED system
- Concealed iHF sensor
- Intelligent soft light start
- Optional basic lighting level 10 %
- High-quality aluminium
- 4-hour manual override (optional)

neva
lux

95 x 331 x 157 mm



L 825 LED iHF silber

Product code **4007841007171**
E-Nr. **924352129**

Technical Data

IDENTIFICATION					
Variant	Silver	Mechanical scalability	No	Luminous flux decline per LM80	L70B10
DIMENSIONS		Radial range	r = 5 m (35 m²)	SETTINGS	
Dimensions L x W x H	95 x 331 x 157 mm	Tangential range	r = 5 m (35 m²)	Twilight switch	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		Twilight setting	2 – 2000 lx
Mains connection	230 – 240 V , 50 / 60 Hz	Colour temperature	3000 K	Time setting	5 sec – 15 min
Power	12 W	Colour rendering index	80-89	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		With illuminant	Yes, STEINEL LED system	Protection class (IP)	IP44
Sensor technology	iHF (intelligent high-frequency technology)	Illuminant	LED cannot be replaced	Protection class	II
Transmission power	< 1 mW	Base	Other	Ambient temperature	-20 – 50 °C
With motion detector	Yes	LED cooling system	Active and Passive Thermo Control	Housing material	Aluminium
Detection angle	160 °	Soft light start	Yes	Cover material	Plastic, opal
Sneak-under protection	Yes	Continuous light	selectable, 4h	SCOPE OF DELIVERY & WARRANTY	
Electronic scalability	Yes	Luminous flux	400 lm	Manufacturer warranty	3 years
		LIFETIME			
		LED lifetime max. °C	50000 h		

L 825 LED iHF silber

Product code **4007841007171**E-Nr. **924352129**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841007171
----------	---------------

E-Number	924352129
----------	-----------

Typ	L 825 LED iHF silber
-----	----------------------

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss