

Dual HF DIM

neva
lux

Product code **4007841002985**

- Optional remote controls
- Optional surface-mounting adapter
- Optional guard cage

neva
lux

120 x 120 x 75 mm



Dual HF DIM

Product code 4007841002985

Technical Data

IDENTIFICATION					
Variant	DIM	Electronic scalability	Yes	With remote control	No
Version	Presence detector	Mechanical scalability	No	Twilight setting teach	Yes
DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	120 x 120 x 75 mm	Radial range	20 x 3 m (60 m²)	Protection class (IP)	IP20
ELECTRICAL		Tangential range	20 x 3 m (60 m²)	Ambient temperature	-25 – 50 °C
Mains connection	240 V, 50 / 60 Hz	Mounting height	2,50 – 3,50 m	Mounting location	ceiling
Number of ECGs DIM interface	50	Optimal mounting height	2,8 m	Application location	Indoors
SENSOR TECHNOLOGY		CONNECTIVITY		Mounting type	Concealed wiring
Sensor technology	High frequency	Networking	Yes	Material	Plastic
HF technology	5,8 GHz	Type of networking	Master/slave, Master/master	Colour	white
Detection angle	360 °	LIGHTING TECHNOLOGY		RAL colour	9010
Opening angle	140 °	Constant light regulation	Yes	SCOPE OF DELIVERY & WARRANTY	
Sneak-under protection	Yes	SETTINGS		Manufacturer warranty	5 years
		Twilight setting	100 – 1000 lx	OTHER	
		Time setting	30 sec – 30 min	Application, location, room	corridor, aisle
		Base light function	Yes		

Dual HF DIM

Product code 4007841002985

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL
---	-------------------------------------

Dual HF DIM

Product code 4007841002985

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841006600	HF-Deckenadapter	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841002985

Typ

Dual HF DIM

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss