

HF 3360 COM1 - Aufputz eckig

neva
lux

Product code 4007841011734

E-Nr. 535940460

- UV-resistant plastic
- Large terminal compartment
- Optional corner wall mount bracket
- Optional remote controls

neva
lux

52 x 95 x 95 mm



HF 3360 COM1 - Aufputz eckig

Product code **4007841011734**
E-Nr. **535940460**

Technical Data

IDENTIFICATION					
Version	Motion detectors	Transmission power	< 1 mW	Time setting	5 s – 15 Min.
DIMENSIONS		HF technology	5,8 GHz	Base light function	No
Dimensions L x W x H	52 x 95 x 95 mm	Detection	also through glass, wood and stud walls	Main light adjustable	No
ELECTRICAL		Detection angle	360 °	Functions	Normal / test mode\nManual ON / ON-OFF
Mains connection	220 – 240 V / 50 – 60 Hz	Opening angle	180 °	Settings via	Remote control\nPotentiometers\nSmart Remote
Power	2000 W	Sneak-under protection	Yes	With remote control	No
Switching output 1 resistive	2000 W	Segment-by-segment masking	No	Twilight setting teach	Yes
Fluorescent lamps ECG	1500 W	Electronic scalability	Yes	HOUSING & MATERIAL	
Fluorescent lamps uncompensated	1000 VA	Mechanical scalability	No	Protection class (IP)	IP54
Fluorescent lamps series-compensated	400 VA	Radial range	Ø 8 m (50 m²)	Ambient temperature	from -20 up to 50 °C
Fluorescent lamps parallel-compensated	400 VA	Tangential range	Ø 8 m (50 m²)	Mounting location	ceiling corner wall
Switching output 1 low-voltage halogen lamps	2000 VA	Mounting height	2,00 – 4,00 m	Application location	Indoors
LED lamps < 2 W	100 W	Optimal mounting height	2,8 m	Mounting type	Surface wiring
LED lamps > 2 W < 8 W	300 W	CONNECTIVITY		Material	Plastic
LED lamps > 8 W	600 W	Networking	Yes	Application room	Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell
Capacitive load in µF	176 µF	Type of networking	Master/master	Colour	white
Switching output 1 number of LED/fluorescent lamps	8 pcs.	Networking via	Cable	RAL colour	9003
SENSOR TECHNOLOGY		LIGHTING TECHNOLOGY		SCOPE OF DELIVERY & WARRANTY	
Max. mounting height	4,00 m	Soft light start	No	Manufacturer warranty	5 years
Sensor technology	High frequency	Continuous light	selectable, 4h	Corner wall bracket included	No
		Constant light regulation	No		
		SETTINGS			
		Twilight switch	Yes		
		Twilight setting	2 – 1000 lx		

HF 3360 COM1 - Aufputz eckig

Product code **4007841011734**
E-Nr. **535940460**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

HF 3360 COM1 - Aufputz eckig

Product code **4007841011734**
E-Nr. **535940460**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841056674	Schwarze Blende für den HF 3360 Aufputz eckig	Coverage
 4007841056698	Schwarze Blende für den HF 3360 Aufputz rund	Coverage
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841035174	Eckwandhalter 3000 weiss	Corner adapter

ORDERING INFORMATION

Art.-Nr.

4007841011734

E-Number

535940460

Typ

HF 3360 COM1 - Aufputz eckig

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss