Hallway COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079468
E-Nr. 535918104

steinel

105 x 103 x 103 mm



Hallway COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079468
E-Nr. 535918104

Technical Data

IDENTIFICATION

Version	Presence detector

DIMENSIONS

Dimensions L × W × H	105 x 103 x 103 mm

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Power	2000 W
Switching output 1 resistive	2000 W
Switching output 1 low-voltage halogen lamps	2000 VA
Own consumption	1 W
Switching output 1 number of LED/fluorescent lamps	8 pcs.
Switching output 1 potential-free	No

SENSOR TECHNOLOGY

Max. mounting height	4,00 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	25 x 3 m (75 m²)
Tangential range	25 x 3 m (75 m²)
Mounting height	2,00 – 4,00 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master Master/slave
Control technology	Steinel Connect
Wireless networking via	BT Open Mesh

LIGHTING TECHNOLOGY

Soft light start	No
Continuous light	selectable
Constant light regulation	No

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	10 s – 60 Min.
Base light function	No
Main light adjustable	No
Functions	Group parameterisation Semi-/fully automatic Lighting scenario Manual ON / ON-OFF Neighbouring group function Normal / test mode
Settings via	Bluetooth
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	Indoors corridor / aisle
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


Hallway COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079468**
E-Nr. **535918104**

Illustrations

TECHNICAL DRAWINGS



105 x 103 x 103 mm

MOUNTING HEIGHT

2,00 – 4,00 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX


Hallway COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079468
E-Nr. 535918104

Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

Hallway COM1 - in-ceiling installation


PRESENCE DETECTOR

EAN 4007841079468
E-Nr. 535918104

Highlights



UV-resistant plastic



Interconnectable and adjustable via Bluetooth

Hallway COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079468**
E-Nr. **535918104**

Accessories

ORDERING INFORMATION

Art.-Nr.	079468
EAN	4007841079468
E-Number	535918104
Typ	**Hallway COM1 - in-ceiling installation**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss