XLED PRO 240 Anthracite

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841057695
E-Nr. 924702412

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80
- Including corner wall mount

221 x 180 x 161 mm



XLED PRO 240 Anthracite

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841057695**
E-Nr. **924702412**

Technical Data

IDENTIFICATION

Variant	**Anthracite**

DIMENSIONS

Dimensions L × W × H	**221 x 180 x 161 mm**

ELECTRICAL

Mains connection	**230 – 240 V**
Power	**20 W**

SENSOR TECHNOLOGY

Max. mounting height	**6,00 m**
Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**240 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Tangential range	**r = 12 m (302 m²)**

CONNECTIVITY

Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Colour temperature	**4000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80-89**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
Luminous flux	**1830 lm**

LIFETIME

LED lifetime max. °C	**60000 h**
Luminous flux decline per LM80	**L70B10**

SETTINGS

Twilight switch	**Yes**

HOUSING & MATERIAL

Impact resistance	**IK00**
Protection class (IP)	**IP44**
Protection class	**II**
Housing material	**Plastic**
Cover material	**Plastic, opal**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**Yes**

XLED PRO 240 Anthracite

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841057695**
E-Nr. **924702412**

Illustrations

MOUNTING HEIGHT

6,00 m
MAX

XLED PRO 240 Anthracite

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841057695**
E-Nr. **924702412**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841057701	**XLED PRO 240 SL anthrazit**	LED Floodlight

ORDERING INFORMATION

Art.-Nr.	4007841057695
EAN	4007841057695
E-Number	924702412
Typ	**XLED PRO 240 Anthracite**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss