

ayana connect LS C440 TW

AYANA

neva
lux

Product code **222006**

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

neva
lux

440 x 95 mm



ayana connect LS C440 TW

Product code 222006

AYANA

Technical Data

DIMENSIONS		LED colour deviation	SDCM3	With program-controlled lighting control	Yes
Dimensions Ø x H	440 x 95 mm	Colour rendering index	80-89	HOUSING & MATERIAL	
ELECTRICAL		Illuminant	LED	Protection class (IP)	IP20
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	5200 lm (Down 4470, Up 730)	Protection class	I
Power	43 W	Beam angle	105°	Ambient temperature	-20...45 °C
Replaceable driver	Yes	Luminaire luminous efficacy	122 lm/W	Housing material	Steel
Type of wiring	Suitable for through wiring	Glare value	UGR < 22	Cover material	Acrylic glass opal
SENSOR TECHNOLOGY		LIFETIME		Mounting type	Ceiling / wall surface-mounted
With motion detector	No	LED lifespan (25 °C)	70000 h	Colour	white
With light sensor	Yes	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
CONNECTIVITY		DALI dimming	Yes	Manufacturer warranty	5 years
With radio network control	Yes	With emergency light	No	CERTIFICATES & EPREL	
LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	No	EPREL energy efficiency class	E
Colour temperature	3000...5600 K				

ayana connect LS C440 TW

Product code 222006

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221103	ayana Diffusor 440 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222006

Typ

ayana connect LS C440 TW

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss