

RS PRO 5150 SC 5C 5 Core (5-core through-wiring)

neva
lux

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079338

E-Nr. 941375609

 **steinel**

1500 x 87 x 58 mm



RS PRO 5150 SC 5C 5 Core (5-core through-wiring)

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079338
E-Nr. 941375609

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Base light function in percent10 – 100 %	
Type of accessory	Other	Measured luminous flux 360°	5940 lm	Base light function percent from	10 %
DIMENSIONS		Colour temperature	4000 K	HOUSING & MATERIAL	
Dimensions L x W x H	1500 x 87 x 58 mm	Illuminant	LED cannot be replaced	Impact resistance	IK07
ELECTRICAL		LIFETIME		Protection class (IP)	IP65
Mains connection	220 – 240 V / 50 – 60 Hz	LED lifetime max. °C	60000 h	Protection class	II
Power	42 W	Luminous flux decline per LM80	L80B10	Ambient temperature	from -20 up to 40 °C
Own consumption	0,45 W	SETTINGS		Housing material	Plastic
SENSOR TECHNOLOGY		Twilight setting	2 – 2000 lx	Cover material	Plastic, structured
Max. mounting height	3,50 m	Time setting	5 s – 60 Min.	Mounting location	ceiling wall
Sensor technology	High frequency	Base light function	Yes	Material	Plastic
With motion detector	Yes	Base light function time	1-60 min	Colour	grey
Detection angle	360 °	Main light adjustable	0 - 100 %	SCOPE OF DELIVERY & WARRANTY	
Opening angle	160 °	Functions	Encrypted communication Neighbouring group function Free selection of the light value in a luminaire group Adjustable fade time when switching on and off Connection to central battery systems Motions sensor Light sensor Orientation light	Manufacturer warranty	5 years
Electronic scalability	Yes			CERTIFICATES & EPREL	
Mounting height	3,50 m			Certificates	DEKRA
CONNECTIVITY				EPREL category	Surrounded product with integrated light source
Networking	Yes				
Networking via	Bluetooth Mesh				

RS PRO 5150 SC 5C 5 Core (5-core through-wiring)


SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079338

E-Nr. 941375609

Illustrations

TECHNICAL DRAWINGS



1500 x 87 x 58 mm

MOUNTING HEIGHT

3,50 m BEREICH	3,50 m MAX
--------------------------------------	----------------------------------


RS PRO 5150 SC 5C 5 Core (5-core through-wiring)

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079338
E-Nr. 941375609


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/slave and master/master interconnection circuit diagram

RS PRO 5150 SC 5C 5 Core (5-core through-wiring)

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079338

E-Nr. 941375609

Highlights



Including STEINEL LED system



Interconnectable and adjustable via Bluetooth



Impact-resistant material rated to IK07



Optional basic lighting level 0 - 100 %



Adjustable mounts for easy installation

RS PRO 5150 SC 5C 5 Core (5-core through-wiring)

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079338
E-Nr. 941375609

Accessories

ORDERING INFORMATION	
Art.-Nr.	079338
EAN	4007841079338
E-Number	941375609
Typ	RS PRO 5150 SC 5C 5 Core (5-core through-wiring)
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	