

ayana DALI P850 4K

AYANA

neva
lux

Product code **221153**

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

neva
lux

850 x 95 mm



ayana DALI P850 4K

AYANA

Product code **221153**

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions Ø x H	850 x 95 mm	Colour rendering index	80-89	Protection class (IP)	IP20
Suspension length	2000 mm	Illuminant	LED	Protection class	I
ELECTRICAL		Luminous flux	9800 lm (Down 8430, Up 1370)	Ambient temperature	-20...45 °C
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	105°	Housing material	Steel
Power	78 W	Luminaire luminous efficacy	126 lm/W	Cover material	Acrylic glass opal
Replaceable driver	Yes	Glare value	UGR < 21	Mounting type	Ceiling pendant
Type of wiring	Suitable for through wiring	LIFETIME		Colour	white
SENSOR TECHNOLOGY		LED lifespan (25 °C)	70000 h	SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	SETTINGS		Manufacturer warranty	5 years
With light sensor	No	DALI dimming	Yes	CERTIFICATES & EPREL	
LIGHTING TECHNOLOGY		With emergency light	No	EPREL energy efficiency class	D
Colour temperature	4000 K	Direct/indirect ratio separately controllable	No		
LED colour deviation	SDCM3				

ayana DALI P850 4K

Product code 221153

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221153

Typ

ayana DALI P850 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss