

RS PRO P1 FLAT SP warmweiss

P-SERIE FLAT

neva
lux

Product code **221820**

- Including STEINEL LED system
- Intelligent soft light start
- Interconnectable by cable (maximum of 10 units)

neva
lux

272 x 64 mm



RS PRO P1 FLAT SP warmweiss

P-SERIE FLAT

Product code 221820

Technical Data

DIMENSIONS		With illuminant		Yes, STEINEL LED system	Protection class (IP)		IP54
Dimensions Ø x H	272 x 64 mm	Illuminant		LED cannot be replaced	Protection class		II
ELECTRICAL		Base		without	Ambient temperature		from -10 up to 40 °C
Mains connection	220 – 240 V / 50 – 60 Hz	LED cooling system		Passive Thermo Control	Housing material		Plastic
Power	8,2 W	Soft light start		Yes	Cover material		Plastic, opal
SENSOR TECHNOLOGY		LIFETIME			Mounting location		ceiling
With motion detector	No	LED lifetime max. °C		60000 h	Application location		Indoors
CONNECTIVITY		LED lifetime L70B50 25°C		> 60000 h	Colour		white
Networking via	Cable	Luminous flux decline per LM80		L80B10	SCOPE OF DELIVERY & WARRANTY		
LIGHTING TECHNOLOGY		SETTINGS			Manufacturer warranty		5 years
Measured luminous flux 360°	922 lm	Main light adjustable		No	CERTIFICATES & EPREL		
Colour temperature	3000 K	HOUSING & MATERIAL			Certificates		DEKRA
		Impact resistance		IK03	EPREL category		Surrounded product with integrated light source

RS PRO P1 FLAT SP warmweiss

Product code **221820**

P-SERIE FLAT

Accessories

ORDERING INFORMATION

Art.-Nr. 221820

Typ RS PRO P1 FLAT SP warmweiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss