

XLED PRO Square eNet - weiss

neva
lux

Product code **4007841009991**

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level
- UV resistant material
- Wireless interconnection
- Remote control RC9 included
- Smart Remote remote control optional

neva
lux

130 x 178 x 230 mm



XLED PRO Square eNet - weiss

Product code 4007841009991

Technical Data

IDENTIFICATION				SETTINGS	
Variant	eNet - white	Segment-by-segment masking	Yes	Twilight switch	Yes
DIMENSIONS		Tangential range	r = 12 m (302 m²)	Twilight setting	2 – 1000 lx
Dimensions L x W x H	130 x 178 x 230 mm	CONNECTIVITY		Time setting	5 sec – 15 min
ELECTRICAL		Networking	Yes	Base light function	Yes
Mains connection	220 – 240 V , 50 / 60 Hz	LIGHTING TECHNOLOGY		Base light function time	10/30 min, all night
Power	24,8 W	Colour temperature	4000 K	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		LED colour deviation	SDCM3	Impact resistance	IK03
Max. mounting height	6,00 m	Colour rendering index	80-89	Protection class (IP)	IP54
Sensor technology	passive infrared	With illuminant	Yes, STEINEL LED system	Protection class	I
With motion detector	Yes	Illuminant	LED cannot be replaced	Ambient temperature	-20 – 40 °C
Detection angle	240 °	LED cooling system	Passive Thermo Control	Housing material	Aluminium
Opening angle	180 °	Luminous flux	2400 lm	Cover material	Plastic, transparent
Sneak-under protection	Yes	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
		LED lifetime max. °C	50000 h	Manufacturer warranty	5 years

XLED PRO Square eNet - weiss

Product code 4007841009991

Illustrations

MOUNTING HEIGHT



XLED PRO Square eNet - weiss

Product code 4007841009991

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841032821	eNet Funk Handsender 2-fach	
 4007841032838	eNet Schaltaktor	

ORDERING INFORMATION

Art.-Nr.

4007841009991

Typ

XLED PRO Square eNet - weiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss