

L 810 LED iHF Z-Wave silber

neva
lux

Product code **4007841029869**

- Including STEINEL LED system
- Concealed iHF sensor
- Intelligent soft light start
- Optional basic lighting level 10 %
- High-quality aluminium
- 4-hour manual override (optional)

neva
lux

145 x 230 x 91 mm



L 810 LED iHF Z-Wave silber

Product code 4007841029869

Technical Data

IDENTIFICATION				LIFETIME	
Variant	Silver	Radial range	r = 5 m (35 m²)	LED lifetime max. °C	50000 h
DIMENSIONS		Tangential range	r = 5 m (35 m²)	Luminous flux decline per LM80	L70B10
Dimensions L x W x H	145 x 230 x 91 mm	Transmission range	Up to 100 m in the open, 30 m indoors	SETTINGS	
ELECTRICAL		LIGHTING TECHNOLOGY		Twilight setting	2 – 1000 lx
Mains connection	220 – 240 V , 50 / 60 Hz	Efficiency	71,5 lm/W	Time setting	5 sec – 15 min
Power	12 W	Colour temperature	3000 K	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		LED colour deviation	SDCM3	Protection class (IP)	IP44
Sensor technology	iHF (intelligent high-frequency technology)	Colour rendering index	80-89	Protection class	II
Transmission power	< 1 mW	With illuminant	Yes, STEINEL LED system	Housing material	Aluminium
Detection angle	160 °	Illuminant	LED cannot be replaced	Cover material	Plastic, opal
Sneak-under protection	Yes	LED cooling system	Active and Passive Thermo Control	SCOPE OF DELIVERY & WARRANTY	
Electronic scalability	Yes	Soft light start	Yes	Manufacturer warranty	3 years
Mechanical scalability	No	Continuous light	selectable, 4h		
		Luminous flux	858 lm		

L 810 LED iHF Z-Wave silber

Product code 4007841029869

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841029876	Smartfriends Box	

ORDERING INFORMATION

Art.-Nr.

4007841029869

Typ

L 810 LED iHF Z-Wave silber

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss