

anele C620

ANELE CONNECT

neva
lux

Product code **221637**

- For universal use for lighting offices, schools, traffic zones, etc.
- Available as intelligent Connect version or as conventional DALI luminaire
- Connect variant with motion detector and powerful IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Microprismatic diffuser for best possible glare control
- Variants available with 595 and 620 mm length
- Surface-mounted housing and installation springs for suspended ceilings available as accessories
- Housing Aluminium RAL9016, white

neva
lux

620 x 620 x 8.5 mm (Einbautiefe: 40 mm)



anele C620

ANELE CONNECT

Product code 221637

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	620 x 620 x 8.5 mm (Einbautiefe: 40 mm)	Colour rendering index	80-89	Protection class (IP)	IP20
		Illuminant	LED	Protection class	I
		Luminous flux	3960 lm	Ambient temperature	-20...45 °C
		Beam angle	90°	Housing material	Aluminum
		Luminaire luminous efficacy	120 lm/W	Cover material	Microprismatic acrylic glass
		Glare value	UGR < 19	Mounting type	In-ceiling installation
ELECTRICAL		LIFETIME		Colour	white
Mains connection	200...240 V / 50 – 60 Hz	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
Power	33 W	SETTINGS		Manufacturer warranty	5 years
Replaceable driver	Yes	DALI dimming	Yes	CERTIFICATES & EPREL	
Type of wiring	Suitable for through wiring	With emergency light	No	EPREL energy efficiency class	E
SENSOR TECHNOLOGY		Suitable for light band configuration	No		
With motion detector	No				
With light sensor	No				
LIGHTING TECHNOLOGY					
Colour temperature	4000 K				
LED colour deviation	SDCM3				

anele C620

ANELE CONNECT

Product code 221637

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221638	anele APG 595	Installation housing
 221639	anele APG 620	Installation housing
 221640	anele DEF	Mounting kit
 221641	anele P-Set	Suspension cable
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221637

Typ

anele C620

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss