

ayana connect LS P850 3K

AYANA

neva
lux

Product code 222029

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

neva
lux

850 x 95 mm



ayana connect LS P850 3K

Product code 222029

AYANA

Technical Data

DIMENSIONS					
Dimensions Ø x H	850 x 95 mm	LED colour deviation	SDCM3	With program-controlled lighting control	Yes
Suspension length	2000 mm	Colour rendering index	80-89	Constant light output control	Yes
ELECTRICAL		Illuminant	LED	HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	9800 lm (Down 8430, Up 1370)	Protection class (IP)	IP20
Power	78 W	Beam angle	105°	Protection class	I
Replaceable driver	Yes	Luminaire luminous efficacy	126 lm/W	Ambient temperature	-20...45 °C
Type of wiring	Suitable for through wiring	Glare value	UGR < 21	Housing material	Steel
SENSOR TECHNOLOGY		LIFETIME		Cover material	Acrylic glass opal
With motion detector	No	LED lifespan (25 °C)	70000 h	Mounting type	Ceiling pendant
With light sensor	Yes	SETTINGS		Colour	white
CONNECTIVITY		DALI dimming	Yes	SCOPE OF DELIVERY & WARRANTY	
With radio network control	Yes	With emergency light	No	Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	No	CERTIFICATES & EPREL	
Colour temperature	3000 K			EPREL energy efficiency class	D

ayana connect LS P850 3K

Product code 222029

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221366	Connect RTC	Real-time clock
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222029

Typ

ayana connect LS P850 3K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss