RS PRO S30 Q SC warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841067526
E-Nr. 941326939

331 x 331 x 56 mm



RS PRO S30 Q SC warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841067526**
E-Nr. **941326939**

Technical Data

DIMENSIONS

Dimensions L × W × H	**331 x 331 x 56 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Power	**26 W**
Own consumption	**0,39 W**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**High frequency**
Transmission power	**< 1 mW**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Segment-by-segment masking	**Yes**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 10 m (79 m²)**
Tangential range	**Ø 10 m (79 m²)**
Mounting height	**2,00 – 4,00 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master**
Slave mode adjustable	**Yes**
Control technology	**Steinel Connect**
Wireless networking via	**BT SIG Mesh**

LIGHTING TECHNOLOGY

Measured luminous flux 360°	**2801 lm**
Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
Base	**without**
LED cooling system	**Passive Thermo Control**
Soft light start	**Yes**
Continuous light	**selectable**

LIFETIME

LED lifetime max. °C	**50000 h**
Luminous flux decline per LM80	**L80B50**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 60 Min.**
Base light function	**Yes**
Base light function detail	**LED effect light**
Base light function time	**1-60 min**
Main light adjustable	**Yes**
Functions	**Group parameterisation Manual ON / ON-OFF Neighbouring group function Presence function Motions sensor Connection to central battery systems DIM function Adjustable fade time when switching on and off Light sensor Normal / test mode Orientation light Presence detector logic Encrypted communication**
Settings via	**Bluetooth**
With remote control	**No**
Twilight setting teach	**Yes**
Base light function in percent	**7 – 100 %**
Base light function percent from	**7 %**

HOUSING & MATERIAL

Impact resistance	**IK03**
Protection class (IP)	**IP20**
Protection class	**II**
Ambient temperature	**from -20 up to 40 °C**
Housing material	**Aluminium**
Cover material	**Plastic, opal**
Mounting location	**ceiling wall**
Application location	**Indoors**
Mounting type	**Surface wiring**
Application room	**Indoors WC / washroom changing room corridor / aisle function room / ancillary room kitchenette outdoors stairwell**
Colour	**Silver**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
House number sheet included	**No**

CERTIFICATES & EPREL

EPREL category	**Surrounded product with integrated light source**


RS PRO S30 Q SC warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841067526**
E-Nr. **941326939**

Illustrations

TECHNICAL DRAWINGS



331 x 331 x 56 mm

MOUNTING HEIGHT

2,00 – 4,00 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX


RS PRO S30 Q SC warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841067526**
E-Nr. **941326939**


Wiring Diagrams

WIRING DIAGRAM 1



Slave/wireless master interconnection circuit diagram

WIRING DIAGRAM 2




Master/master interconnection circuit diagram

RS PRO S30 Q SC warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841067526**
E-Nr. **941326939**

Highlights




Including STEINEL LED system



Intelligent LED cooling system



Optional basic lighting level 10 - 50 %



Interconnectable and adjustable via Bluetooth



High-quality aluminium



Optional remote control RC10

RS PRO S30 Q SC warm white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841067526**
E-Nr. **941326939**

Accessories

ORDERING INFORMATION

Art.-Nr.	067526
EAN	4007841067526
E-Number	941326939
Typ	**RS PRO S30 Q SC warm white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss