# RS D2 S

**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN 4007841052539
E-Nr. 941300559

- Indoor light with motion detector, with brushed stainless steel frame
- With pleasant ambient light for a beautiful room atmosphere, suitable for ceiling and wall mounting
- Automatic light thanks to hidden 360° high-frequency sensor with up to Ø8 m detection on movement
- Functions: adjustable basic light, 4 hours continuous light
- Warm white light (3000 K) and long-life 8,8 W LEDs with 886 lm
- Incl. mounting accessories - plastic-free packaging

steinel

66 x 300 x 300 mm



# RS D2 S

**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN **4007841052539**
E-Nr. **941300559**

# Technical Data

## DIMENSIONS

| | |
|---|---|
| Dimensions L × W × H | **66 x 300 x 300 mm** |

## ELECTRICAL

| | |
|---|---|
| Mains connection | **220 – 240 V / 50 – 60 Hz** |
| Power | **8,8 W** |
| Own consumption | **0,38 W** |

## SENSOR TECHNOLOGY

| | |
|---|---|
| Max. mounting height | **4,00 m** |
| Sensor technology | **High frequency** |
| Transmission power | **< 1 mW** |
| HF technology | **5,8 GHz** |
| With motion detector | **Yes** |
| Detection | **also through glass, wood and stud walls** |
| Detection angle | **360 °** |
| Opening angle | **160 °** |
| Segment-by-segment masking | **No** |
| Electronic scalability | **Yes** |
| Mechanical scalability | **No** |
| Radial range | **Ø 8 m (50 m²)** |
| Tangential range | **Ø 8 m (50 m²)** |
| Mounting height | **2 – 4 m** |
| Optimal mounting height | **2,8 m** |

## CONNECTIVITY

| | |
|---|---|
| Networking | **No** |
| Control technology | **On/Off-Leuchte** |

## LIGHTING TECHNOLOGY

| | |
|---|---|
| Measured luminous flux 360° | **886 lm** |
| Colour temperature | **3000 K** |
| LED colour deviation | **SDCM3** |
| With illuminant | **Yes, STEINEL LED system** |
| Illuminant | **LED cannot be replaced** |
| Base | **without** |
| LED cooling system | **Passive Thermo Control** |
| Soft light start | **No** |
| Continuous light | **selectable, 4h** |

## LIFETIME

| | |
|---|---|
| LED lifetime max. °C | **50000 h** |
| Luminous flux decline per LM80 | **L70B10** |

## SETTINGS

| | |
|---|---|
| Twilight switch | **Yes** |
| Twilight setting | **2 – 2000 lx** |
| Time setting | **5 s – 15 Min.** |
| Base light function | **Yes** |
| Base light function time | **10/30 min, all night** |
| Settings via | **Potentiometers** |
| With remote control | **No** |
| Twilight setting teach | **No** |
| Base light function in percent | **10 %** |
| Base light function percent from | **10 %** |

## HOUSING & MATERIAL

| | |
|---|---|
| Impact resistance | **IK03** |
| Protection class (IP) | **IP20** |
| Protection class | **II** |
| Ambient temperature | **from -10 up to 40 °C** |
| Housing material | **Plastic** |
| Cover material | **Plastic, opal** |
| Mounting location | **ceiling wall** |
| Application location | **Indoors** |
| Mounting type | **Surface wiring** |
| Application room | **Indoors WC / washroom corridor / aisle function room / ancillary room outdoors stairwell** |
| Colour | **white** |

## SCOPE OF DELIVERY & WARRANTY

| | |
|---|---|
| Manufacturer warranty | **3 years** |

## CERTIFICATES & EPREL

| | |
|---|---|
| EPREL category | **Surrounded product with integrated light source** |


# RS D2 S

**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN **4007841052539**
E-Nr. **941300559**

## Illustrations

### TECHNICAL DRAWINGS




66 x 300 x 300 mm

### MOUNTING HEIGHT

| 2 – 4 m | 2,8 m | 4,00 m |
|---|---|---|
| BEREICH | OPTIMAL | MAX |


# RS D2 S

**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN **4007841052539**
E-Nr. **941300559**

## Wiring Diagrams

### WIRING DIAGRAM 1





Circuit diagram

# RS D2 S

**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN **4007841052539**
E-Nr. **941300559**

## Highlights




**Including STEINEL LED system**



**LED ambient light**



**Optional basic lighting level 10 %**



**4-hour manual override (optional)**



**High-quality materials**

# RS D2 S

**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN **4007841052539**
E-Nr. **941300559**

## Accessories

| | ARTICLE NUMBER | DESCRIPTION | CATEGORY |
|---|---|---|---|
|  | 4007841006358 | **Ersatzhaube für RS D2 S** | Spare Part |

**ORDERING INFORMATION**

| | |
|---|---|
| Art.-Nr. | 052539 |
| EAN | 4007841052539 |
| E-Number | 941300559 |
| Typ | **RS D2 S** |

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss