

IS 3180 DALI-2 APC - concealed, sq.

MOTION DETECTOR

neva
lux

EAN 4007841055738

E-Nr. 535942508

 **steinel**

78 x 94 x 94 mm



IS 3180 DALI-2 APC - concealed, sq.

MOTION DETECTOR

EAN 4007841055738
E-Nr. 535942508

Technical Data


IDENTIFICATION		Optimal mounting height		2 m	Base light function in percent		10 – 50 %
Version		Motion detectors			Base light function percent from		10 %
DIMENSIONS		CONNECTIVITY			HOUSING & MATERIAL		
Dimensions L x W x H		Networking		Yes	Protection class (IP)		IP20
78 x 94 x 94 mm		Type of networking		Master/slave	Ambient temperature		from -20 up to 50 °C
ELECTRICAL		Networking via		Cable	Mounting location		corner wall
Mains connection		LIGHTING TECHNOLOGY			Application location		Indoors Outdoors
220 – 240 V / 50 – 60 Hz		Soft light start		Yes	Mounting type		Concealed wiring
Control output DALI		Continuous light		selectable, 4h	Material		Plastic
Broadcast 1x30 electronic ballasts		Constant light regulation		Yes	Application room		Indoors all round the building corridor / aisle courtyard & driveway function room / ancillary room multi-storey / underground car park outdoors stairwell
SENSOR TECHNOLOGY		SETTINGS			Colour		white
Max. mounting height		Twilight switch		Yes	RAL colour		9003
Sensor technology		Twilight setting		2 – 1000 lx	SCOPE OF DELIVERY & WARRANTY		
Detection angle		Time setting		5 s – 15 Min.	Manufacturer warranty		5 years
Opening angle		Base light function		Yes	Corner wall bracket included		No
Sneak-under protection		Base light function time		1-30 min all night	CERTIFICATES & EPREL		
Segment-by-segment masking		Main light adjustable		50 - 100 %	Certificates		DALI-2
Electronic scalability		Functions		Normal / test mode Manual ON / ON-OFF Constant-lighting control ON-OFF			
Mechanical scalability		Settings via		Remote control Potentiometers Smart Remote			
Radial range		With remote control		No			
r = 3 m (14 m²) / r = 4 m (25 m²)		Twilight setting teach		Yes			
Tangential range							
r = 6 m (57 m²) / r = 20 m (628 m²)							
Switching zones							
448 switching zones							
Mounting height							
1,80 – 2,50 m							

IS 3180 DALI-2 APC - concealed, sq.
MOTION DETECTOR

EAN 4007841055738
E-Nr. 535942508

Illustrations

TECHNICAL DRAWINGS



78 x 94 x 94 mm

MOUNTING HEIGHT


1,80 – 2,50 m BEREICH	2 m OPTIMAL	2,50 m MAX
--------------------------	----------------	---------------

IS 3180 DALI-2 APC - concealed, sq.
MOTION DETECTOR

EAN 4007841055738
E-Nr. 535942508


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Circuit diagram for interconnecting DALI-2 APC with DALI-2 IPD

IS 3180 DALI-2 APC - concealed, sq.

MOTION DETECTOR

EAN 4007841055738

E-Nr. 535942508

Highlights



UV-resistant plastic




Optional remote controls

IS 3180 DALI-2 APC - concealed, sq.
MOTION DETECTOR

EAN 4007841055738
E-Nr. 535942508

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841056728	Schwarze Blende für IR-Sensoren Unterputz eckig	Accessory

ORDERING INFORMATION

Art.-Nr.

055738

EAN

4007841055738

E-Number

535942508

Typ

IS 3180 DALI-2 APC - concealed, sq.

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss